



Product Data Sheet

Woodfree Paper/Water Based Permanent/ White Glassine

92C1422

Facestock

Woodfree paper

A white wood free uncoated paper with non-glare surface.

Color	White	
Basic Weight	70 (± 2)g/m ²	ISO-536
Thickness	84 (± 2) μ	ISO-534

Adhesive

Water based permanent

A water based acrylic permanent adhesive providing good tack and adhesion to a wide variety of substrates including apolar surfaces. Complies with FDA 175.105 recommendation for food contact.

Initial Tack	8 N/25mm	FTM9
Peel adhesion 90°	6 N/25mm	FTM1
Min.Appl.Temp.	+5 °C	
Service Temp.	-20 °C to 120°C	

Liner

One side siliconised white glassine

Color	white	
Basic Weight	60(± 2)g/m ²	ISO-536
Thickness	50 (± 2) μ	ISO-534

Application

Suitable for general purposes including address, blank and logistic labels.

Printing Methods

Provides very good printability on most conventional printing technologies including water-based and UV flexo, UV letterpress. Good die-cutting and stripping properties.

Shelf life

- 1 year if stored at following condition:
- Store in a cool and dry place, and keep the material in original packaging when not used.
 - Temperature 23 \pm 2°C .
 - Humidity 50 \pm 5%.
 - Keep away from direct sunlight.

• The above data has been typically tested in our own laboratory but it does not represent as guarantee of all purpose. In order to ensure the correct usage of our products, further testing on the corresponding substrates to verify the result is always recommended.