



Product Data Sheet

Tamperfas Vinyl/Solvent Based Permanent/Art Paper

12S0136

Facestock

Tamperfas Vinyl

A matt white cast vinyl film which will break apart with any attempt to remove label after applying onto substrate.

Color	Matt White	
Basic Weight	130 (±5)g/m ²	ISO-536
Thickness	70 (±5)μ	ISO-534

Adhesive

Solvent based permanent

A clear solvent permanent adhesive for general purpose industrial applications, providing good initial tack and adhesion to a wide variety of substrates including medium to low surface energy.

Initial Tack	7 N/25mm	FTM9
Peel adhesion 90°	8 N/25mm	FTM1
Min.Appl.Temp.	+5 °C	
Service Temp.	-5 °C to 40°C	

Liner

One side siliconised art paper

Color	white	
Basic Weight	170 (±5)g/m ²	ISO-536
Thickness	165 (±5)μ	ISO-534

Application

It is a frangible film designed specifically for security labeling, special care should be taken in particular die-cutting and stripping process.

Printing Methods

It is printable with most conventional printing, such as flexographic and UV letterpress.

Shelf life

6 months if stored at following condition:

- Store in a cool and dry place, and keep the material in original packaging when not used.
- Temperature 23±2°C .
- Humidity 50 ±5%.
- Keep away from direct sunlight.

• The above data has been typically tested in our own laboratory but it does not represent as guarantee of all purpose. In order to ensure the correct usage of our products, further testing on the corresponding substrates to verify the result is always recommended.