

# ComIn I3000

**High Performance Industrial Grade 4G Wireless Router**

## Product Specifications



- Rich Data and Communication Interfaces
- External 6dBi Omni-Directional Antenna
- 1200Mbps Dual Band Access Point
- High Transmit Wi-Fi Power for Wider Coverage
- Built-in M.2 Connector Interface for 5G Function Expansion

## Product Description

ComIn I3000 is an industrial 4G wireless router that integrates multiple functions such as WIFI transmission, local resource sharing, cellular mobile Internet access, precise GPS positioning, serial port pass-thru transmission, and backend remote management. It provides more processing performance, richer interfaces and higher network connection speed than ordinary industrial routers. This product is suitable for different application types and scenarios, such as car WIFI, video transmission, PLC remote control, smart express cabinet, video surveillance, etc.

## Product Features

- Dual-core processor, faster and more powerful processing speed
- 4G LTE modem Cat4, can be customized to Cat6 modem
- Industrial grade design, support use in high and cold temperature
- Full Metal enclosure, higher safety index, better corrosion resistance
- Gigabit Network Port Design for faster link communication
- Support network port function definition and customization
- Support Wi-Fi 802.11b/g/n/ac up to 1200Mbps max. data speed
- Maximum Wi-Fi user connection exceeds 60+
- Wide Power Voltage Design
- Linkable to external serial device
- USB3.0 high speed interface port
- Optional dedicated precise GPS positioning (optional)
- Hardware watchdog design prevents downtime and auto-recovery

## Main Features – Industrial Application Design

- Adopt high performance 32-bit dual-core network processor
- Wide voltage input design: 9 ~ 36V

- Industrial grade software and hardware watchdog design, trouble free and reliable operation in power station, transportation, and industrial control environment application
- Excellent electromagnetic, radiation, static protection ability
- Industrial grade EMC electromagnetic compatibility and radiation performance, passed the GB/T17626.5-2008 Level 4 test standard
- Industrial grade components, working temperature: -30 ~ +70°C
- Industrial enclosure, suitable for extreme environments
- Fan-less heat dissipation technology effectively reduces the failure rate of the equipment
- SIM card protection design
- Meet the trouble-free and reliable operation under vibration and shock environment

## **Main Features – Rugged, Stable and Reliable**

- Dual watchdog design ensure that the stability of the system
- Apply complete anti-disconnection mechanism that to ensure the end data terminal is always online
- The product passed EMC test requirements
- The Ethernet interface built-in 1.5KV electromagnetic isolation protection GB/T17626.5-2008 (Level 4)
- SIM/UIM interface built-in 1.5KV ESD protection GB/T17626.5-2008 (Level 4)
- Built-in reserve phase protection and overvoltage protection for the power interface

## **Hardware Specifications**

### **Main Hardware**

CPU	MTK7621
Flash	128Mbit
RAM	DDR2 1Gbit

## Wi-Fi Specifications

Wi-Fi Standard	Dual Band Wi-Fi, IEEE 802.11ac/b/g/n
Data Rate	IEEE 802.11g: Max 54Mbps IEEE 802.11n: Max. 300Mbps IEEE 802.11ac: Max 900Mbps
Encryption	WEP / WPA / WPA2 / WPA3
RF Power	20 ± 2dBm
Reception Sensitivity	<-72dBm @ 54Mbps

## Wi-Fi Specifications

Wi-Fi Standard	Dual Band Wi-Fi, IEEE 802.11ac/b/g/n
Data Rate	IEEE 802.11g: Max 54Mbps IEEE 802.11n: Max. 300Mbps IEEE 802.11ac: Max 866Mbps
Encryption	WEP / WPA / WPA2 / WPA3
RF Power	20 ± 2dBm
Reception Sensitivity	<-72dBm @ 54Mbps

## 4G/3G/2G Cellular Specifications

LTE Category	LTE Cat 4	
Frequency*	CN Version	LTE-FDD: B1, B3, B5, B7,B8,B20 LTE-TDD: B34, B38, B39, B40, B41 WCDMA: B1, B5, B8 GSM: B3, B8
	EU Version	LTE-FDD: B1, B3, B5,B7, B8, B20, B28 LTE-TDD: B38, B40, B41 WCDMA: B1,B5, B8
	LATAM/AU Version (Custom)	LTE-FDD: B1, B2, B3, B4, B5, B7, B8, B28, B66 LTE-TDD: B40 WCDMA: B1, B2, B4, B5, B8 GSM: B2, B3, B5, B8

Data Rate	LTE	LTE-FDD: Max. 150 (DL)/ Max. 50 (UL) LTE-TDD: Max. 130 (DL)/ Max. 30 (UL)
	DC-HSPA+	Max. 21 (DL)/ Max. 5.76 (UL)
	WCDMA	Max. 384 (DL)/ Max. 384 (UL)
	EDGE	Max. 236.8 (DL)/ Max. 236.8 (UL)
	GPRS	Max. 85.6 (DL)/ Max. 85.6 (UL)
Transmitting Power	Class 4 (33dBm±2dB) for EGSM900 Class 1 (30dBm±2dB) for DCS1800 Class E2 (27dBm±3dB) for EGSM900 8-PSK Class E2 (26dBm±3dB) for DCS1800 8-PSK Class 3 (24dBm+1/-3dB) for WCDMA bands Class 3 (23dBm±2dB) for LTE-FDD bands Class 3 (23dBm±2dB) for LTE-TDD bands	

Note \*: The information about the supported standards and wireless bands may vary with the application of 4G modules. Before ordering, please ask and confirm with our sales representatives whether or not the required network standards and wireless frequency bands are met.

## Interfaces

WAN	1 x 10/100M/1000M Ethernet Port, Auto MDI/MDIX, Built-in 1.5KV Electromagnetic Isolation Protection
LAN	4 x 10/100M/1000M Ethernet Port, Auto MDI/MDIX, Built-in 1.5KV Electromagnetic Isolation Protection
SIM Card	2 x Push-Push SIM card Slot
USB	1 x USB 3.0 Port
UART	1 x RS232 or RS485 Serial Communication
Power	1 x Standard DC Connector, Built-in Power Reverse Protection
Antenna	1 x 4G Antenna 2 x 2.4GHz Wi-Fi Antenna 2 x 5GHz Wi-Fi Antenna 1 x GPS Antenna
LED Indicators	1 x SYS System Status Indicator 4 x LAN Ethernet Status indicator 1 x WAN Ethernet Status Indicator 2 x WIFI Status Indicator 1 x NET Internet Indicator 1 x GPS Status Indicator

Reset	1 x Pin-hole Reset Button
-------	---------------------------

## Power Supply

Input Power	DC 12V/1.5A
Power Range	DC 9~30V
Power Consumption	<2A (12V)

## Physical Properties

Enclosure	Metal Enclosure, Industrial Protection Grade IP30. The enclosure and the system are safely isolated, and are widely used in automotive and specific industrial applications.
Dimensions	200mm x 141mm x 28mm
Weight	920g

## Environments

Operating Temperature	-30°C to +70°C
Storage Temperature	-40°C to +90°C
Humidity	95% (non-condensing)

## Product Views



## Order Information

Order Code	Product Description
ComIn I3000	1 x I3000 Wireless Router unit 1 x Spring Magnetic Antenna (4G) 2 x Dipole/Rubber-Duck Antenna (2.4GHz Wi-Fi) 2 x Dipole/Rubber-Duck Antenna (5GHz WI-FI) 1 x GPS Antenna (Optional) 1 x AC/DC Power Adapter 1 x Network Cable



To see more MovingComm products,

Visit:-

Movingcomm official website <http://www.movingcomm.com/en>

Movingcomm Alibaba global site: <https://movingcomm.en.alibaba.com>

INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH MOVINGCOMM PRODUCTS. NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. EXCEPT AS PROVIDED IN MOVINGCOMM'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, MOVINGCOMM ASSUMES NO LIABILITY WHATSOEVER, AND MOVINGCOMM DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO SALE AND/OR USE OF MOVINGCOMM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. UNLESS OTHERWISE AGREED IN WRITING BY MOVINGCOMM, THE MOVINGCOMM PRODUCTS ARE NOT DESIGNED NOR INTENDED FOR ANY APPLICATION IN WHICH THE FAILURE OF THE MOVINGCOMM PRODUCT COULD CREATE A SITUATION WHERE PERSONAL INJURY OR DEATH MAY OCCUR.

MovingComm may make changes to specifications and product descriptions at any time, without notice. Buyers must receive a confirmation from MovingComm prior using the product. MovingComm shall have no responsibility whatever for conflicts or incompatibilities arising from future changes to them.

Copyright © 2013-2021 Shenzhen MovingComm Technology Co., Ltd. All rights reserved.

## 深圳星恒讯科技有限公司

SHENZHEN MOVINGCOMM TECHNOLOGY CO., LTD.

Addr: 4F, No. 5 Building, TongFuKang ShuiTian Industrial Zone,  
ChangCheng Road, ShuiTian Community, ShiYan, BaoAn  
District, 518108 ShenZhen, GuangDong, China

Tel: 86-755-23125215

Fax: 86-755-23125215-802

Email: [sales@movingcomm.com](mailto:sales@movingcomm.com)

