

Comin SL240H

24 Port Gigabit PoE Switch

Product Specifications



- Support IEEE 802.3at/af Power-over-Ethernet protocol
- Dual SFP Fiber Optical Port
- 24-Port Gigabit Ethernet Port
- 400W High Power
- Switch to enable or disable VLAN



Product Description

ComIn-SL240H is a medium-sized enterprise-class POE switch. The product is equipped with 2 SFP optical ports and 24 x 10M/100M/1000M adaptive electrical ports. Each network port supports a maximum of 30W POE power supply, and the switch supports a maximum of 400W POE power supply. The product has the characteristics of high performance, easy installation, and easy maintenance, which greatly saves manpower and material costs in the network deployment. Products are widely used in such as small and medium-sized enterprises, conference rooms, urban villages, hotels, Internet cafes, shopping malls and other places.

Product Features

- Designed for CCTV/Security/Wireless AP Area.
- PoE chipset support 802.3af/at standard, which have overcurrent and overload protection, once the
 current to PD device is too high, it will cut off to make sure safe to use. Much safer and long life compared
 with same cheap PoE switch with MCU (Micro Controller Unit).
- Design product life is 3 years, with high frequency low resistance capacitor, guarantee the more stable performance.
- Single port support IEEE 802.3at protocol, maximum PoE power up to 30W, comply with all IEEE 802.3af/at standard PD equipment.
- Products passed rigorous testing in package loss rate, PPM, load detection.
- Support port VLAN division such as port Isolation to protect ports.
- 100~240V wide voltage design, can work well all over the world.

Product Specifications

Model	ComIn SL240H
Standard	IEEE802.3 10 BASE-T Ethernet IEEE802.3u 100 BASE-TX Fast Ethernet IEEE802.3ab 1000BASE-T GIGABIT Ethernet ANSI/IEEE 802.3 NWay Auto-negotiation IEEE802.3af IEEE802.3at
Interface	24 x 10M/100M/1000M RJ45 ports support POE power supply 2 x 10M/100M/1000M uplink port 2 x 1000M SFP optical port



Port Properties	Connector: RJ-45, SFP Supports 10M/100M/1000M Mbit/s rate Supports half-duplex, full duplex, self-negotiation working mode Support MDI/MDI-X Self-adaptation
Network Cable	10/100/1000 BASE-TX 3/4/5 twisted pair, supports maximum transmission distance of 100 meters
Features	With On/Off switch to enable/disable VLAN (port isolation)
LED Light	Each Port: Link/Act Indicator Each Device: Power Indicator
Backplane Bandwidth	56Gbps
Forwarding Rate	10Mbps: 14800pps 100Mbps: 148000pps 1000Mbps: 148000pps
Switch Mode	Storage and Forwarding Mode
MAC Address Table	MAC Address Auto-Learning and Auto-Aging. Max MAC address table: 8K
PoE+ Power Supply	Single port maximum power: 30W, Whole device power: 400W (Model: SL240H)
Size	440mm x 221.5mm x 45mm
Input Power	400W AC 100 V∼240 V, 50/60 HZ
Working Temperature	0°C ~ 40 °C
Heat Dissipate	Internal fan cooling

Order Information

Order Code	Product Description
ComIn SL240H	1 x 24-Port PoE Switch 1 x Power Cord



To see more MovingComm products,

Visit:-

Movingcomm official website http://www.movingcomm.com/en Movingcomm Alibaba global site: https://movingcomm.en.alibaba.com

INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH MOVINGCOMM PRODUCTS. NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. EXCEPT AS PROVIDED IN MOVINGCOMM'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, MOVINGCOMM ASSUMES NO LIABILITY WHATSOEVER, AND MOVINGCOMM DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO SALE AND/OR USE OF MOVINGCOMM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. UNLESS OTHERWISE AGREED IN WRITING BY MOVINGCOMM, THE MOVINGCOMM PRODUCTS ARE NOT DESIGNED NOR INTENDED FOR ANY APPLICATION IN WHICH THE FAILURE OF THE MOVINGCOMM PRODUCT COULD CREATE A SITUATION WHERE PERSONAL INJURY OR DEATH MAY OCCUR.

MovingComm may make changes to specifications and product descriptions at any time, without notice. Buyers must receive a confirmation from MovingComm prior using the product. MovingComm shall have no responsibility whatever for conflicts or incompatibilities arising from future changes to them.

Copyright © 2013-2022 Shenzhen MovingComm Technology Co., Ltd. All rights reserved.

深圳星恒讯科技有限公司

SHENZHEN MOVINGCOMM TECHNOLOGY CO., LTD.

Addr: 4F, No. 5 Building, TongFuKang ShuiTian Industrial Zone, ChangCheng Road, ShuiTian Community, ShiYan, BaoAn District, 518108 ShenZhen, GuangDong, China

Tel: 86-755-23125215

Fax: 86-755-23125215-802

Email: sales@movingcomm.com

