

ComFi WK9530

High Performance Outdoor 2100Mbps WiFi5 Triple Band High Power Wireless AP

Product Specifications



- External 6dBi Omni-Directional Antenna
- Qualcomm Chipset Solution, up to 120 devices
- Waterproof Outdoor Casing, IP67 Protection
- Standard PoE Power Input or DC Power Input (Optional)
- 2100Mbps Triple Band, Adjustable Tx Power 802.11AC MIMO
- FIT and FAT AP Mode, Adjustable TX Power, Coverage Radius 200 Meters



Product Description

ComFi WK9530 is an outdoor 2x2 triple-band 802.11ac Wave 2 wireless AP, suitable for outdoor areas that require wireless coverage such as scenic spots, parks, schools, and squares. ComFi WK9530 supports MIMO, the maximum concurrent connection rate of triple-band can reach up to 2100Mbps, which can build a stable and high-speed wireless network for users. ComFi WK9530 has high-performance wireless indicators, can get a larger wireless coverage area and better wall penetration performance. ComFi WK9530 supports the access of hundreds of wireless terminals to meet the application scenarios of high-density wireless terminals. At the same time, ComFi WK9530 also has good compatibility and supports the access of most wireless terminals on the market. Users can easily connect using mobile phones, tablets or laptops.

ComFi WK9530 integrates the OpenWrt development platform. For teams that have software development capabilities but lack a hardware platform, and want to develop their own wireless 11ac AP, WK9530 is a very good choice. Users can quickly and easily develop upper-layer applications according to specific needs, and create their own unique wireless AP products.

ComFi WK9530 supports PoE power supply and pole installation, and the installation and configuration are flexible and convenient. Users only need to spend a short time to complete the settings, you can enjoy the fun of surfing the Internet

Product Features

- Support pole installation
- Support 2.4G 2x2 Wi-Fi (802.11b/g/n/ac), up to 300Mbps wireless rate
- Support 2 x 5G 2x2 Wi-Fi (802.11a/n/ac Wave 2), up to 1734Mbps wireless rate
- Two 2.4GHz band antennas and four 5GHz band antennas
- 1 RJ45 1GbE WAN port, supporting 802.at PoE (PD)
- 1 SFP Gigabit optical port (optional)
- 6 N-type antenna interfaces
- 5 status indicators (PWR/ WAN/ 2.4G/ 5G)

Hardware Specifications

Model	WK9530		
Dimension	240mm x 195mm x 80mm (L x W x H)		
Weight	Approx. 2500g		
Installation	Wall or Pole Installation		
LED Indicators	PWR / SYS / 2.4GHz / 5GHz / SFP		

	1 x GbE Uplink, Support 802.3at Power Supply					
Interfaces	1 x 1GbE SFP Port (Optional)					
	6 x N-Type Antenna Connector (Wi-Fi)					
Power Input	50V ~ 57V, 802.3at PSE					
Environment						
Operating Temperature	-40°C to +65°C					
Storage Temperature	-40°C to +70°C					
Operating Humidity	5% - 95% (non-condensing)					
Air Pressure	86kPa ~ 106kPa Altitude					
IP Rating	IP67					
Safety Certification	SRRC, Can do according customer's request					
Stability						
Annual Failure Rate	AFR < 1.5% (Continuous Operation Status)					
Chipset Solution						
CPU	Qualcomm IPQ4019 + QCA8075 + QCA9886					
Flash	32MB SPI Flash					
RAM	256MB DDR3L Memory					
Wi-Fi Characteristics						
Working Frequency	2.4GHz Radio: 2.4000GHz ~ 2.4835GHz					
	5GHz Radio: 5.150~5.250,5.250~5.350,5.470~5.725, 5.725~5.850GHz					
Max. Transmit Power	2.4GHz Radio: 27dBm (500mW) @ MCS0, 25dBm @ MCS7					
	5GHz Radio: 27dBm (500mW) @ MCS0, 20dBm @ MCS7					
	2.4G Radio:					
Data Rate	802.11b: 1, 2, 5.5, and 11Mbps					
	802.11g: 6, 9, 12, 18, 24, 36, 48, and 54Mbps					
	802.11n HT20/ HT40: MCS0~MCS15 (400/ 800ns GI)					
	5G Radio:					
	802.11a: 6, 9, 12, 18, 24, 36, 48 and 54Mb/s					
	802.11n HT20/ HT40: MCS0~MCS15(400/ 800ns GI)					
	802.11ac VHT20/VHT40/VHT80: MCS0 ~ MCS9(400/ 800ns GI)					



		802.11g: -92dBm@6Mbps -74dBm@54Mbps					
	802.11n:	802.11n:					
			HT20		HT40		
	MCS0/8/16		-90dBm		-87dBm		
	MCS7/15		-71dBm		-68dBm		
Reception Sensitivity	802.11a: -89dBm@6Mbps -74dBm@54Mbps 802.11ac: MCS0 -90dBm -87dBm -84dBm MCS8 -67dBm -61dBm -58dBm						
Antenna Specification	Frequency (MH	Frequency (MHz)		2400 ~ 2500		4940 ~ 5850	
	Polarization	Polarization		Horizontal / Vertical		Horizontal / Vertical	
	Gain (dBi)	Gain (dBi)		6~8		6~8	



Order Information

Product Model	Product Description
ComFi WK9530	Complete Product Unit including 1 x 48V PoE Power Supply (Optional) / 12VDC Power Adapter (Optional) 2 x Omni-Directional Fiberglass Antenna (2.4GHz WIFI) 4 x Omni-Directional Fiberglass Antenna (5GHz WIFI) 1 x Mounting Bracket Outdoor 1 x Network Cable



To see more MovingComm products,

Visit:-

Movingcomm official website http://www.movingcomm.com/en Movingcomm Alibaba global site: https://movingcomm.en.alibaba.com

INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH MOVINGCOMM PRODUCTS. NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. EXCEPT AS PROVIDED IN MOVINGCOMM'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, MOVINGCOMM ASSUMES NO LIABILITY WHATSOEVER, AND MOVINGCOMM DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO SALE AND/OR USE OF MOVINGCOMM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. UNLESS OTHERWISE AGREED IN WRITING BY MOVINGCOMM, THE MOVINGCOMM PRODUCTS ARE NOT DESIGNED NOR INTENDED FOR ANY APPLICATION IN WHICH THE FAILURE OF THE MOVINGCOMM PRODUCT COULD CREATE A SITUATION WHERE PERSONAL INJURY OR DEATH MAY OCCUR.

MovingComm may make changes to specifications and product descriptions at any time, without notice. Buyers must receive a confirmation from MovingComm prior using the product. MovingComm shall have no responsibility whatever for conflicts or incompatibilities arising from future changes to them.

Copyright © 2013-2021 Shenzhen MovingComm Technology Co., Ltd. All rights reserved.

深圳星恒讯科技有限公司

SHENZHEN MOVINGCOMM TECHNOLOGY CO., LTD.
Addr: 4F, No. 5 Building, TongFuKang ShuiTian Industrial Zone, ChangCheng Road, ShuiTian Community, ShiYan, BaoAn District, 518108 ShenZhen, GuangDong, China
Tel: 86-755-23125215
Fax: 86-755-23125215-802
Email: sales@movingcomm.com

