



ELECTRICAL CHARACTER:

- a. 100% OPEN&SHORT TESTING;
- b. WITHSTANDING VOLTAGE:DC 300V 0.01Sec;
- c. INSULATION RESISTANCE:10M Ohm(Min);
- d. CONDUCTIVE RESISTANCE:2 Ohm(Max).

A	INITIAL RELEASE		13/03/02	
REV	DESCRIPTION OF CHANGE		DATE	
TOLERANCE INCHES			M/M	
.X	.015	.30	<b>OIKWAN</b> 东莞市嵩群实业有限公司 DONGGUAN OIKWAN INDUSTRIAL CO., LTD.	
.XX	.010	.10		
.XXX	.005	.05		
DRAWN BY	TONY CHAN	SCALE	NONE	REV A
		UNIT	MM	
CHECK BY		SHEET	1/3	COSTOMER:
		DATE	16/11/17	
CUSTOMER. P/N:		TITLE: MINISAS HD 4x TO 4x		
P/N: AQ-1-MS44102000		P/N: AQ-1-MS44102000		

4	MOLDING	AQ-3-GL100501	PA,BALCK	A/R	KG
3	ASSEMBLY PARTS	AQ-3-MS62001	MINISAS HD ASSEMBLY <Zinc ALLOY HOODS, HOOK,PULL-TAB, RUBBER RING>	2	set
2	PCBA	AQ-3-MS31021	MINISAS HD 4X PCBA, PIN,30u Au, 100±10 Ohm	4	PCS
1	CABLE	AQ-3-MS41602	<30AWG*2C+D+HMAM+HM>*8C+M+AM+B,OD:6.8 MM,BLACK PVC JACKET 100±5 Ohm	A/R	mm
NO.	PART NAME	PART NO	SPEC DESCRIPTION	QT'Y	UNIT