



NOTE:
 1.100% OPEN&SHORT TESTING,
 2.INSULATION: 10M Ω hm MIN DC: 300V
 3.CONDUCTIVE: 2 Ω hm MAX
 4.100% FUNCTIONAL TESTING

						A	INITIAL RELEASE			18/08/10
						REV	DESCRIPTION OF CHANGE			DATE
6	CONN	AQ-3-GL52B01	DB9/M,G/F	1	pcs	TOLERANCE			OIKWAN [®] DONGGUAN AIQUN INDUSTRIAL CO.,LTD SCALE: NONE UNIT: MM SHEET: 1/1 DATE: 18/08/10 TITLE: DB9/M-USB ADAPTER P/N: AQ-1-CV116DM01	
5	SCREW	AQ-3-GL21007	SREW, ϕ 2.3*20mm	2	pcs	.X	.015	.30		
4	CONN.	AQ-3-GL52601	USB A/M,G/F	1	pcs	.XX	.010	.10		
3	MOLDING	AQ-3-GL100101	LDPE	A/R	9	.XXX	.005	.05		
2	MOLDING	AQ-3-GL145201BK	45P PVC,BLACK	A/R	9	DRAWN BY	TONY CHAN		REV	A
1	PCBA	AQ-3-DB31004	PCBA,FR4,FT232+ZT213,W13.5*L35*T1.2mm	1	PCS	CHECK BY			CUSTOMER:	
NO.	PART NAME	PART NO.	SPEC DESCRIPTION	QT'Y	UNIT	CUSTOMER P/N:				