



NOTE:  
 1.100% OPEN&SHORT TESTING,  
 2.INSULATION: 10M Ωhm MIN DC: 300V  
 3.CONDUCTIVE: 2 Ωhm MAX  
 4.100% FUNCTIONAL TESTING



NO.	PART NAME	PART NO.	SPEC DESCRIPTION	QT'Y	UNIT	CUSTOMER P/N:	P/N: AQ-1-DB11602	
7	CONN	AQ-3-GL52B01	DB9/F,G/F	1	pcs	A	INITIAL RELEASE	
6	SCREW	AQ-3-GL21007	SREW,φ2.3*37mm	2	pcs	REV	DESCRIPTION OF CHANGE	
5	CONN.	AQ-3-GL52601	USB A/M,G/F	1	pcs	TOLERANCE		
4	MOLDING	AQ-3-GL100101	LDPE	A/R	9	INCHES		
3	MOLDING	AQ-3-GL145201BK	45P PVC,BLACK	A/R	9	MM		
2	PCBA	AQ-3-DB31001	PCB WHIT FT232RL+ZT213CHIP,W13.5*L27.5*T1.2mm	1	PCS	.X .015 .30		
1	CABLE	AQ-3-DT40402BK	<28AWG*1P*AL+24AWG*2C>*AL+B;DD:5.0MM,BLACK PVC	A/R	mm	.XX .010 .10		
							.XXX .005 .05	
							DRAWN BY	TONY CHAN
							CHECK BY	
							SCALE	NONE
							UNIT	MM
							SHEET	1/1
							DATE	18/08/10
							REV	A
							CUSTOMER:	
							DWG NO:	
							TITLE:	DB9/F-USB

**DIKWAN**® DONGGUAN AIQUN INDUSTRIAL CO., LTD