


Pinout

| P1 | P2 |
|-----|------|
| NC | PIN1 |
| GND | PIN2 |
| RXD | PIN3 |
| TXD | PIN4 |
| GND | PIN5 |
| NC | PIN6 |



NOTE:
 1.100% OPEN&SHORT TESTING,
 2.INSULATION: 10M Ωhm MIN DC: 300V
 3.CONDUCTIVE: 2 Ωhm MAX
 4.100% FUNCTIONAL TESTING

| NO | NAME | Description | QTY | Unit |
|----|---------|--|-----|------|
| 6 | MOLDING | 45P PVC, BLACK COLOR, MOLDED, ROHS | 1 | PCS |
| 5 | MOLDING | RJ12 MALE, STANDARD SIZE, TRANSPARENT, ROHS | 1 | PCS |
| 4 | CONN. | USB TYPE A MALE, ROHS | 1 | PCS |
| 3 | PCB | PCBA WITH FT232RL+ZT213CHIP, USB RS232, ROHS | 1 | PCS |
| 2 | CONN. | RJ12MALE, 6P6C, GOLD PLATED CONTACTS | 1 | SET |
| 1 | CABLE | 28AWG, 6C, BARE COPPER, BLACK PVC JACKET, ROHS | 1 | PCS |

| A | INITIAL RELEASE | | 13/03/02 | |
|----------------|-----------------------|-------------------|----------|------|
| REV | DESCRIPTION OF CHANGE | | | DATE |
| TOLERANCE | | | | |
| INCHES | | M/M | | |
| .X | .015 | .30 | | |
| .XX | .010 | .10 | | |
| .XXX | .005 | .05 | | |
| DRAWN BY | | TONY CHAN | | REV |
| CHECK BY | | | | A |
| CUSTOMER. P/N: | | P/N: AQ-1-RJ12602 | | |

OIKWAN 东莞市嵩群实业有限公司
 DONGGUAN OIKWAN INDUSTRIAL CO., LTD.

SCALE NONE UNIT MM

SHEET 1/3 CUSTOMER: DATE 16/9/20 DWG NO.:

TITLE: USB TO RJ12