



NOTE:
 1.100%OPEN&SHORT TESTIGN,
 2.INSULATION RESISTANCE 10M Ohm MIN DC300V
 3.CONDUCTIVE RESISTANCE: 2 Ohm MAX

12	LATCH	AQ-3-MS21008	STAINLESS STEEL	1	pcs
11	MOLDING	AQ-3-GL100401	PBT+30GF% BLACK	A/R	9
10	PCBA	AQ-3-MS31019	MINI SAS 36PIN PCB, PIN:15u' Au, 105±10 ohm	1	PCS
9	EXPANDD	AQ-3-MS76001	PET BALCK OD: 10mm	A/R	mm
8	MOLDING	AQ-3-GL10101	LDPE NATURAL	A/R	9
7	ACETATE TAPE	AQ-3-MS77001	W=25±5mm	A/R	mm
6	CONN	AQ-3-MS51C02	OCULINK 4I CONN PIN:Au 15u	1	PCS
5	PCB	AQ-3-MS31022	OCULINK 4I PCB 88±8 ohm	1	PCS
4	HOOK	AQ-3-MS64002	OCULINK 4I HOOK_UP PC+ABS, BLACK	1	PCS
3	HOOK	AQ-3-MS64001	OCULINK 4I HOOK_DOWN PC+ABS, BLACK	1	PCS
2	CABLE	AQ-3-MS20101	30AWG CABLE	A/R	mm
1	CABLE	AQ-3-MS40207	(32AWG*2C+2D)AL+MYLAR,OD:0.65*1.54MM,85±5 ohm.	A/R	mm
NO.	PART NAME	PART NO.	SPEC DESCRIPTION	QT'Y	UNIT

WIRING TABLE

P1		P2	
RESERVED	A1	B1	GND
GND	A2	B2	Tx0+
Rx0+	A3	B3	Tx0-
Rx0-	A4	B4	GND
GND	A5	B5	Tx1+
Rx1+	A6	B6	Tx1-
Rx1-	A7	B7	GND
GND	A8	B8	SB
SB	A9	B9	SB
SB	A10		
GND	A11		
SB	A12	B10	SB
SB	A13	B11	SB
GND	A14	B12	GND
Rx2+	A15	B13	Tx2+
Rx2-	A16	B14	Tx2-
GND	A17	B15	GND
Rx3+	A18	B16	Tx3+
Rx3-	A19	B17	Tx3-
GND	A20	B18	GND
RESERVED	A21		
RESERVED	B1	A1	GND
GND	B2	A2	Rx0+
Tx0+	B3	A3	Rx0-
Tx0-	B4	A4	GND
GND	B5	A5	Rx1+
Tx1+	B6	A6	Rx1-
Tx1-	B7	A7	GND
GND	B8	A8	SB
SB	B9	A9	SB
SB	B10		
GND	B11	A10	SB
SB	B12	A11	SB
GND	B13	A12	GND
GND	B14	A13	Rx2+
Tx2+	B15	A14	Rx2-
Tx2-	B16	A15	GND
GND	B17	A16	Rx3+
Tx3+	B18	A17	Rx3-
Tx3-	B19	A18	GND
GND	B20		
RESERVED	B21		

A	INITIAL RELEASE		20/06/27
REV	DESCRIPTION OF CHANGE		DATE
	TOLERANCE INCHES	M/M	DIKWAN® DONGGUAN AIQUN INDUSTRIAL CO., LTD.
.X	.015	.30	
.XX	.010	.10	
.XXX	.005	.05	
DRAWN BY	TONY CHAN	SCALE	NONE
		UNIT	MM
CHECK BY		SHEET	1/1
		DATE	22/06/27
CUSTOMFR P/N		P/N: AQ-1-MS811010500	