



ELECTRICAL CHARACTER:

- a. 100% OPEN&SHORT TESTING;
- b. WITHSTANDING VOLTAGE:DC 300V 0.01Sec;
- c. INSULATION RESISTANCE:10M Ohm(Min);
- d. CONDUCTIVE RESISTANCE:2 Ohm(Max).

NO.	PART NAME	PART NO	SPEC DESCRIPTION	QT'Y	UNIT	CUSTOMER. P/N:	P/N: AQ-1-MS421012000
7	MOLDING	AQ-3-GL100601	PA, BLACK	A/R	KG	A	INITIAL RELEASE 13/03/02
6	ASSEMBLY PARTS	AQ-3-MS62002	MINISAS HD ASSEMBLY <Zinc ALLOY HOODS, HOOK,PULL-TAB, RUBBER RING>	1	set	REV	DESCRIPTION OF CHANGE DATE
5	PCBA	AQ-3-MS31024	MINISAS HD 4X PCBA, PIN,30u Au, 100±10 Ohm	2	PCS	TOLERANCE INCHES M/M	
4	MOLDING	AQ-3-GL100101	LDPE RDHS	A/R	KG	.X	.015 .30
3	ASSEMBLY PARTS	AQ-3-MS62001	MINISAS 26P ASSEMBLY <Zinc ALLOY HOODS, HOOK,PULL-TAB, RUBBER RING>	1	set	.XX	.010 .10
2	PCBA	AQ-3-MS31021	MINISAS 26P PCBA, PIN,15u Au, 100±10 Ohm	1	PCS	.XXX	.005 .05
1	CABLE	AQ-3-MS41602	<30AWG*2C+D+HMAM+HM>*8C+M+AM+B,OD:6.8 MM,BLACK PVC JACKET 100±5 Ohm	A/R	mm	DRAWN BY TONY CHAN	
						CHECK BY	SCALE NONE UNIT MM
						SHEET 1/3 CUSTOMER: DONGGUAN AIQUN INDUSTRIAL CO.,LTD.	
						DATE 15/03/02 DWG NO.:AQ13-021	
						TITLE: MINI SAS HD 4x TO MINISAS 26P	
						REV A	