



NOTES:
 1.100% OPEN&SHORT WITH MISS WIRE TEST
 2.TEST CONDITION:
 1).CONDUCTANCE RESISTANCE:2 ohm
 2).SHORT OPEN DETERMINANT:20K ohm
 3).INSULATION RESISTANCE:10M ohm AT DC300V.

| | | | | | |
|-----|--------------|---------------|---|------|------|
| 8 | LATCH | AQ-3-MS21008 | STAINLESS STEEL | 4 | pcs |
| 7 | LABLE | AQ-5-MS5039 | W7*L25, PRINT "P1&P2&P3&P4" | 8 | pcs |
| 6 | ACETATE TAPE | AQ-3-MS77001 | W=25±5mm | 2 | pcs |
| 5 | EXPANDO | AQ-3-MS76001 | PET BALCK DD: 10mm | A/R | mm |
| 4 | MOLDING | AQ-3-GL100101 | LDPE,NATURAL | A/R | g |
| 3 | MOLDING | AQ-3-GL145201 | 45P PVC BLACK | A/R | g |
| 2 | CONN. | AQ-3-GL51S01 | SATA 7P/F,PIN:G/F | 8 | PCS |
| 1 | CABLE | AQ-3-MS40208 | (30AWG*2C+2d)*AL+MYLAR,DD:0.97*2.17MM,100±5 ohm | A/R | mm |
| NO. | PART NAME | PART NO. | SPEC DESCRIPTION | QT'Y | UNIT |

| | | | | |
|---------------------|-----------------------|------|--|--|
| A | INITIAL RELEASE | | 25/07/14 | |
| REV | DESCRIPTION OF CHANGE | | DATE | |
| TOLERANCE | | | DIKWAN® DONGGGUAN AIQUN INDUSTRIAL CO., LTD. | |
| INCHES | | | SCALE | |
| MM | | | NONE | |
| .X | .015 | .030 | UNIT MM | |
| .XX | .010. | .010 | SHEET 1/1 | |
| .XXX | .005 | .005 | CUSTOMER: | |
| DRAWN BY TOMY CHANG | | | DATE 25/07/14 | |
| CHECK BY | | | DWG No.:AQ14119 | |
| CUSTOMER P/N: | | | TITLE:4xSATA to 4xSATA RA | |
| | | | P/N: AQ-1-MSSS4R10500 | |