

## Cut Length of Sleeves

Model: HSS-W  $\Phi$ 457\*2.5-450

HSS-W: Heat Shrinkable Wraparound Sleeves

$\Phi$ 457-----Joint or Pipeline Dimete

2.5-----Thickness (1.5,1.8,2.0,2.7,2.9,3.0) mm

450-----Roll Width (150,200,300,350,400,500,550,600,700) mm

Pipe Outside Diameter		Sleeve length	Patch Width	Total Epoxy Primer
Inch	mm	mm	mm	A B g
4	114	478	100	50
6	168	648	100	88
8	213	789	100	122
10	273	977	100	151
12	325	1141	100	180
14	355	1235	100	197
16	406	1395	100	225
18	457	1555	120	254
20	508	1715	120	282
22	558	1872	120	233
24	609	2032	120	338
26	660	2192	120	366
28	711	2353	120	394
30	762	2513	150	423
32	813	2673	150	451
34	864	2833	150	479
36	914	2990	150	507
38	965	3150	150	535
40	1016	3310	150	564
42	1067	3470	150	620
44	1118	3631	150	648
46	1168	3788	150	676
48	1219	3948	150	700
50	1270	4108	150	733
52	1320	4267	150	750
54	1422	4586	150	789
56	1473	4746	150	800
58	1524	4905	150	846

Note: Tolerances on Sleeves length are:  $\pm 1$  inches

Tolerances on Patch width are:  $\pm 0.25$  inches

Tolerances on Total Epoxy Primer weight are:  $\pm 5g$