

型号Model		NF200DFM NF200SFM	NF250DFM NF250SFM	NF300DFM NF300SFM
参数 Technical Date				
名义制冷量 Nominal Capacity (kW)		3.3	4.3	4.6
匹数 Horse Power (HP)		2	2.5	3
压缩机 Compressor		MLM015	MLM019	MLM021
风机个数 Fan Quantity		1	1	1
风叶直径 Fan Diameter (mm)				
风量 Air Flow (m <sup>3</sup> /h)		6300	6300	6300
风机功率 Fan Motor Power (W)		≤170	≤170	≤170
连接管管径 Connection Pipe Diameter	液管 Liquid Line (inch)	3/8	3/8	3/8
	气管 Gas Line (inch)	3/4	3/4	3/4
电源 Power Surch		220V/1/50Hz	220V/1/50Hz	220V/1/50Hz
		380V/3/50Hz	380V/3/50Hz	380V/3/50Hz
额定电流 Rated Current (A)		11.4/4.8	13.6/5.7	14.7/6.1
外形尺寸 External Dimensions	宽 Width (mm)	1050	1050	1050
	高 Height (mm)	845	845	845
	深 Deep (mm)	430	430	430
净重 Net Weight (kg)		73	74	82

注：制冷剂R22，环境温度32℃，蒸发温度-10℃，吸气温度20℃。

Remark:R22 refrigerant,Duty at 32℃ ambient temperature,-10℃ Evaporating t

NF350DFM NF350SFM	NF400DFM NF400SFM	NF500SFM	NF600SFM	NF700SFM	NF800SFM
5.7	6.8	8.1	9.3	10.6	12.3
3.5	4	5	6	7	8
MLM026	MLM030	MLM038	MLM045	MLM048	MLM058
1	1	2	2	2	2
490					
6300	6300	10800	10800	10800	10800
≤170	≤170	≤340	≤340	≤340	≤340
1/2	1/2	1/2	1/2	1/2	1/2
3/4	3/4	7/8	7/8	7/8	7/8
220V/1/50Hz	220V/1/50Hz	380V/3/50Hz	380V/3/50Hz	380V/3/50Hz	380V/3/50Hz
380V/3/50Hz	380V/3/50Hz				
15.3/7.2	18.6/8.5	10.6	12.5	13.5	15.5
1050	1050	1050	1050	1050	1200
845	845	1245	1245	1245	1245
430	430	430	430	430	580
94	100	105	116	120	134

temperature, 20°C suction temperature