

Version: 1.0

Manta E1066 Water-in-oil Emulsifier

Description

Manta E1066 is a lipophilic alkyl-containing polyether polydimethylsiloxane with excellent W/Si and W/O emulsifying capabilities. It has good emulsifying capabilities for silicone oil and non-silicone oil esters. It has outstanding stability and excellent dispersion ability for powder raw materials.

Typical Physical Properties

INCI/CTFA Lauryl PEG-9 Dimethicone Ethyl Dimethicone

Appearance Colorless to light yellow transparent to translucent liquid

Refractive index (25°C) 1.4250-1.4350 Specific gravity (25°C) 0.900-0.950 Viscosity (cSt, 25°C) 400-800

Properties

Alkyl polyether polydimethylsiloxane;

Excellent W/Si, W/O emulsifying ability, good emulsification stability;

Easy to emulsify and can be operated at low temperature;

Good emulsifying ability for silicone oil and non-silicon oil esters;

Silky and non-sticky skin feel;

Applications

Manta E1066 can be used in a variety of personal care products, including: skin care, makeup, and sunscreen products.

How to use

Under rapid stirring, slowly add the water phase into the oil phase in portions and stir quickly evenly. Increasing the stirring speed can improve the stability of the emulsion system, and adding antifreeze agents such as propylene glycol and glycerol can improve the antifreeze effect of the product. Increasing the proportion of water phase can increase the viscosity of the system.

Before adding water to emulsify, the oil and emulsifier should be stirred evenly;

If all raw materials are liquid, they can be emulsified at room temperature without homogenization, and a stable emulsion can be obtained by rapid stirring;

Adding electrolyte (0.5~2% sodium chloride) solution to the aqueous phase can improve the storage



Technical Data Sheet

Version: 1.0

stability of the emulsion system.

The recommended usage level is 0.3%-5%.

Packaging

In 200L drum, IBC

Safety and Storage

Keep away from heat and open flame. Prevent from the exposure of moisture, acid, alkalis and other impurities. When stored at well in the original unopened containers, this product has a usable life of 24 months from the date of production (drum packing).

Contact Information

Nanjing Manta New Material Co., Ltd

Add: Jiangbei new district, Nanjing (210031), China.

Mob: 0086 18962800162

Mail: inquiry@mantasil.com Web: www.mantasil.com