



Xinfeng Company Profile

About Xinfeng

Zhengzhou XinFeng Machinery Manufacturing Co.,Ltd, which was founded in 1989, located in China, has a well established history in the R&D and production of concrete machinery.

With over 40+years of experience, Xinfeng has been TOP10 manufacturer of concrete machinery in China, being customer-oriented and designing tailor-made engineering solution spreaded in all over the world.

Xinfeng Staff

With a total area of 120,000 m², Xinfeng's employees is 300-500 people this year. Design departments for each of the production areas, a service and spare parts department, a commissioning department, a sales department, a technical control department, a logistics department.





Concrete Mixer JS500-JS1500

Main technical parameter

Model		JS3000	JS2000	JS1500	JS1000	JS7500	JS500
Discharge Capacity(L)		3000	2000	1500	1000	750	500
Charge Capacity(L)		4800	3200	2400	1600	1200	800
Theory productivity(m ³ /h)		≤180	≤120	≤90/75	≤60/50	≤35	≤25
Max.aggregate diameter(mm)		≤80/120	≤80/100	≤60/80	≤60/80	≤40/60	≤40/50
Working cycle time(s)		60	60	60/72	60/72	72	72
Total weight(kg)		9200	8800	7500	5500	5000	3000
Outline dimension(mm)	Transporting	4050×2680×2150	3500×2400×2152	4200×2200×3000	3800×2200×2800	3110×2620×2580	3050×2530×2680
	Operating			9530×3400×1080	10460×3400×9050	5025×3100×5680	4461×3050×4180
Agitating vane	Rotational speed (r/min)	21	24.5	23.5	29.6	26	26
	Count	2×10	2×8	2×8	2×8	2×7	2×7
Agitator motor	Model	Y280L-6	Y250M-6	Y180L-4	Y180L-4		
	Power(KW)	2×55	2×37	2×30	2×18.5	30	18.5
Hoist motor	Model			YEZ180L-4	YEZ160L-4	Y132M-4	YEZ132S-4
	Power(KW)			18.5	15	7.5	5.5
Pump motor	Model			80JDB-45	80JDB-45	BL18-16-1.1	BL12-12-1.1
	Power(KW)			3	3	1.1	1.1





Pan Concrete Mixer

Main technical parameter

Model	JW350	JW500	JW750	JW1000	JW1500
Capacity	0.35m ³	0.5m ³	0.75m ³	1m ³	1.5m ³
Motor power	5.5KW	7.5KW	11KW	15KW	18.5KW
Size	1.1m×0.4m	1.3m×0.4m	1.5m×0.4m	1.8m×0.5m	2m×0.5m
Thickness	4mm×6mm	6mm×6mm	6mm×8mm	6mm×8mm	8mm×10mm

Model	JW2000	JW3000	JW4000	JW5000
Capacity	2m ³	3m ³	4m ³	5m ³
Motor power	22KW	30KW	37KW	45KW
Size	2m×0.6m	2.2m×0.8m	2.3m×1m	2.5m×1m
Thickness	8mm×10mm	10mm×10mm	10mm×10mm	12mm×10mm



**Concrete Drum Mixer——JZM series****Main technical parameter**

	Model	JZM350	JZM500	JZM750	JZM1000	JZM1500	JZM2000
Nature of work	Discharge capacity	350L	500L	750L	1000L	1500L	2000L
	Feeding capacity	560L	800L	1200L	1600L	2200L	2700L
	Productivity	13 m ³ /h	18-20m ³ /h	30-35m ³ /h	45-50m ³ /h	50-60m ³ /h	60-65m ³ /h
	Mixing drum rotating speed	15r/min	15r/min	12.26r/min	15-17r/min	15-17r/min	17-20r/min
	Max. aggregate particle	60mm	60mm	80mm	80mm	80mm	80mm
	Precision of water supply	Error≤2%	Error≤2%	Error≤2%			
Electric motor	Agitator motor	5.5KW	2x5.5KW	2x7.5KW	2x11KW	2x11KW	2x15KW
	Lifting motor	4.5KW	5.5KW	7.5KW	7.5KW	7.5KW	7.5KW
	Pump motor	0.75KW	1.1KW	1.1KW	1.1KW	1.1KW	1.1KW
Tire specifications		650-16	700-16	750-16			
Maximum towing speed		20km/h	20km/h	20km/h			
Outline dimension(L*W*H)		3800*2050*2690	5710*2350*5050	6216*2300*6060	6350*2400*6060	6570*2520*6700	6540*2700*6750
Total weight		1970kg	4100kg	5500kg	3400kg	4300kg	5300kg





Concrete Drum Mixer——JZC series

Main technical parameter

Model	JZC350	JZC400	JZC500
Feeding capacity	560L	640L	800L
Discharge capacity	350L	400L	500L
Productivity	10-14m ³ /h	12-16m ³ /h	18-20m ³ /h
Agitator motor	5.5kw	5.5kw	7.5KW
Lifting motor	4.5kw	4.5kw	4.5KW
Pump motor	0.55kw	0.55kw	0.55KW
Maximum towing speed	14r/min	14r/min	14r/min
Max.aggregate particle	40-60mm	40-60mm	60-80mm
Outline dimension(L*W*H)	226*199*275cm	276*214*300cm	332*246*365cm
Total weight	1250kg	1350kg	1500kg

