

## 主要技术参数

规格型号 Type	筛面尺寸 Screen Size(mm)	层数 Layer	安装角度 Installation slope	最大进料粒度 Max Feed Size (mm)	处理能力 Process Capacity (T/H)	振动频率 Vibrating Frequency (r/min)	双振幅 Double Amplitude (mm)	电机型号 Motor Type	电机功率 Motor Power	机器重量 Weight (T)	外形尺寸 Dimensions (L×W×H) (mm)
YK1545	1500×4500	1	20°	400	23-180	970	7-8	Y180L-6	15	3.2	4945×2138×912
2YK1545	1500×4500	2	15°	400	23-180	970	7-8	Y180L-6	15	3.9	5141×2245×1210
3YK1545	1500×4500	3	15°	400	23-180	970	7-8	Y180L-6	15	4.8	5219×2245×1630
4YK1545	1500×4500	4	15°	400	23-180	970	7-8	Y180L-6	15	5.7	5441×2245×2086
YK1860	1800×6000	1	18°	400	40-288	970	7-8	Y180L-6	15	4.4	6286×2406×1162
2YK1860	1800×6000	2	18°	400	40-288	970	7-8	Y180L-6	15	5.5	6783×2597×1300

3YK186 0	1800×600 0	3	18°	400	40-288	970	7-8	Y200L <sub>2</sub> -6	22	7.7	6864×2608×167 0
4YK186 0	1800×600 0	4	18°	400	40-288	970	7-8	Y200L <sub>2</sub> -6	22	9.4	7010×2608×212 0
YK2160	2100×600 0	1	18°	400	70-400	970	7-8	Y180L-6	15	5.5	6242×2908×117 0
2YK216 0	2100×600 0	2	18°	400	70-400	970	7-8	Y200L <sub>2</sub> -6	22	6.6	6732×2953×134 0
3YK216 0	2100×600 0	3	18°	400	70-400	970	7-8	Y250M- 6	37	8.8	6888×2953×194 5
4YK216 0	2100×600 0	4	20°	400	70-400	970	7-8	Y280M- 6	45	11	7083×2953×220 0
YK2460	2400×600 0	1	20°	400	128-520	970	7-8	Y200L <sub>2</sub> -6	22	4	6468×3545×117 0
2YK246 0	2400×600 0	2	20°	400	128-520	970	7-8	Y225M- 6	30	7	6753×3300×132 0
3YK246 0	2400×600 0	3	20°	400	128-520	970	7-8	Y250M- 6	37	8.6	6932×3300×181 6
4YK246 0	2400×600 0	4	20°	400	128-520	970	7-8	Y280M- 6	45	10	7117×3300×232 0
2YK247 0	2400×700 0	2	20°	400	160-600	970	7-8	Y250M- 6	37	6.8	7776×3300×132 0
3YK247 0	2400×700 0	3	20°	400	160-600	970	7-8	Y280M- 6	45	8.5	7958×3300×182 0
4YK247 0	2400×700 0	4	20°	400	160-600	970	7-8	Y280M- 6	45	12.5	8140×3300×232 0

2YK307 2	3000×720 0	2	20°	400	180-670	970	7-8	Y200L <sub>2</sub> -6	22*2	13.7	8146×3913×167 0
3YK307 2	3000×720 0	3	20°	400	180-670	970	7-8	Y225M- 6	30*2	14.2	8307×3913×221 4