

H.265 18X Zoom 1080P WiFi Speed Dome IP Camera



Features

- * 4" double layer metal body construction, IP66 rate protection
- * HD Imager Sensor, 18X optical zoom
- * HD-IP digital interface output, 2.0MP high definition image
- * PWM function, intelligent IR illumination & power consumption is variable, dependant the zoom factor
- * IR distance 60M
- * ONVIF2.4 compatible; good compatibility with NVRs like DAHUA, HIKVISION , JUFENG and AXXON , Milestone and so on
- * APP: Eseecloud

Dimension



Accessories

Instruction book

Warrant card

Screw fittings

Desiccant

	Model Number	WDM-IP8854F-Wifi
Camera		
Image Sensor	HI3516E+ SC2232	
Effective Pixels	2.0MP(1920x1080)	
Resolution Ratio	1920*1080@20fps	
Auto Control IR LED	PWM	
Lens	f=6mm-108mm(18X Zoom)	
Leds	6 pcs IR led	
IR distance	Up to 60 meters	
Dome		
Rotation Range	Pan: 0°~360°, Tilt: 0°~93°	
Pan rotation speed	45°/s	
Tilt rotation speed	30°/s	
Auto Flip	Horizontal 180°, Vertical 93°	
A-B scan	User programmable(scan speed 1-9 levels setting available)	
Preset points	220	
Inspection teams	3 groups(Max.16 points, dwell time user selectable)	
Mechanical zero calibration	Support	
WiFi and Network		
WIFI Protocol	802.11b/g/n	
Wireless distance	≥150M	
WiFi Safe mode	WEP\WPA\WPA2	
WiFi antenna	Enhanced 5db antenna	
Mobile View	Support android/ios smart phone	
APP	Eseecloud	
TF card storage	Supports 128G	
Software Control	Software Control	
Software Control	PELCO instruction set	
Video and Audio		
Video Compression	H.265/H.264/M-JPEG	
Voice intercom	Built-in microphone and speaker	
Audio Compression	AAC	
General		
waterproof	IP66	
Power	DC12V3A	
Operating temperature	-40°C ~+60°C	
Consumption	≤ 15W	
Lightning Protection	Transient voltage 6000V	