



- * Hisilicon high-performance DSP
- * H.264 High profile dual stream
- * Standard ONVIF Protocol
- * Support motion detection, P2P, ONVIF
- * Support ICR filter switching function, day and night surveillance
- * Support remote control by smart phone, iPhone/Android
- * Support power supply DC12V
- * **APP: XMEYE**

Specification

Product Name	H.264 1.0/1.3/2.0MP P2P ONVIF Mini Full HD UFO Hidden IP Camera		
Model No.	WDM-IP64FDA	WDM-IP64FDB	WDM-IP64FDH
Video			
System	Embedded linux		
Output resolution	1280(H)×720(V)	1280(H)×960(V)	1920(H)×1080(V)
D/N Mode	ICR-CUT		
Illumination	0.5Lux/F1.2(Led on)		
Video processing	H.264 video compression, dual streaming		
Video Output	Main streaming: 1280×720,1024×768,1280×720; Sub streaming: 1280x720, 960x540, 640x360, 480x270, 352x288, 320x 240	Main streaming: 1280*960, 1280×720, 1024×768,1280×720; Sub streaming: 1280x720, 960x540, 640x360, 480x270, 352x288, 320x 240	Main streaming: 1920*1080, 1280*960, 1280×720,1024×768,1280×720; Sub streaming: 1280x720, 960x540, 640x360, 480x270, 352x288, 320x 240
Frame rate	1.0MP 25/30 frame(full real time),support 1~30frame/seconds adjustable	1.3MP 25/30 frame(full real time),support 1~30frame/seconds adjustable	2.0MP 25/30 frame(full real time),support 1~30frame/seconds adjustable
Network interface	RJ45 ethernet,10/100M;RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP protocol supported		
Access Protocol	Standard ONVIF Protocol, Support third party access;		
	Support IE6.0 and aboveSmartphone		
	Support Android\iPhone		
Lens			
Lens	2.5/3.7mmPinhole lens, or 3.6/4/6mm MTV board lens for optionally		
Function			
Function	Support motion detection		
	Support front end storage ,playback and download		
	Support uniform client and platform system application		
Normal			
Power supply	DC12V		
Operation temperature	-10℃~-+50℃		
Size	75mm*55mm*68mm		