

FS4028 Size:40*40*28mm DC Axial Fan



Frame:Thermal Plastic,UL 94V-0
 Impeller:Thermal Plastic,UL 94V-0
 Lead Wire:AWG#26 UL1007(Optional)
 (+):Red(-):Black
 Insulation Resistance:
 Above 10M Between Lead wire and Frame DC500V

Specification:

Model	Bearing	Rated voltage(v)	Rated current (A)	Rated Input power(W)	Nominal speed (RPM)	Air flow		Air pressure		Noise (dB)	Weight(g)
						(CFM)	(m ³ /min)				
FS4028H DA12B(S)	sleeve/ball	12	0.35	4.20	10000	14.31	0.40	8.55	0.34	38.0	35
FS4028M DA12B(S)	sleeve/ball	12	0.25	3.00	9000	12.88	0.36	7.71	0.30	36.0	
FS4028L DA12B(S)	sleeve/ball	12	0.18	2.16	8000	11.45	0.32	6.85	0.27	34.0	
FS4028H DA24B(S)	sleeve/ball	24	0.25	6.00	10000	14.31	0.40	8.55	0.34	38.0	
FS4028M DA24B(S)	sleeve/ball	24	0.18	4.32	9000	12.88	0.36	7.71	0.30	36.0	
FS4028L DA24B(S)	sleeve/ball	24	0.12	2.88	8000	11.45	0.32	6.85	0.27	34.0	