

## Quotation

To: Rey Bantilan

**SPECIFICATION OF PRODUCTS:**

Item	Model	Features	Unit Price
Portable Autoclaves	YX-LM 	<b>LPG or Electric heated dual-use</b> 1. Fully stainless steel structure. 2. Double scale indication pressure gauge. 3. Easy to operate, safe and reliable.	12L: USD145 18L: USD150 24L: USD225
	YX-LD 	<b>Electric heated</b> 1. Fully stainless steel structure. 2. Double scale indication pressure gauge. 3. Easy to operate, safe and reliable.	18L: USD175 24L: USD240
	YX-HM 	<b>LPG or Electric heated dual-use, Quickly open</b> 1. Fully stainless steel structure. 2. Rated working pressure: 0.14-0.16Mpa. Rated working temperature: 126°C.	18L: USD215 24L: USD300

	<p style="text-align: center;">YX-LDJ</p> 	<p><b>Electric heated,Timing,Temper. control</b></p> <ol style="list-style-type: none"> <li>1. Fully stainless steel structure.</li> <li>2.Indicator light shows working status.</li> <li>3.Double scale indication pressure gauge.</li> <li>4.Time can be set arbitrarily at 0-60 min</li> <li>5.After sterilization,the buzzer reminds automatic stop.</li> <li>6.Easy to operate,safe and reliable.</li> </ol>	<p>18L:USD235 24L:USD280</p>
<p>Portable Autoclaves</p>	<p style="text-align: center;">YX-HDJ</p> 	<p><b>Electric heated,Quickly open,Water automatic cuts off</b></p> <ol style="list-style-type: none"> <li>1. Fully stainless steel structure.</li> <li>2.Hand wheel type of quick-open door structure.</li> <li>3.Indicator light shows working status.</li> <li>4.Double scale indication pressure gauge.</li> <li>5.Time can be set arbitrarily at 0-60 min</li> <li>6.After sterilization,the buzzer reminds automatic stop.</li> </ol>	<p>18L:USD420 24L:USD465</p>
	<p style="text-align: center;">YX-HDD</p> 	<p><b>Electric heated,Automatic computer control</b></p> <ol style="list-style-type: none"> <li>1.Fully stainless steel structure.</li> <li>2.Quickly open structure.</li> <li>3.Digital display working status.</li> <li>4.After sterilization,the buzzer reminds automatic stop.</li> <li>5.Easy to operate,safe and reliable.</li> </ol>	<p>18L:USD510 24L:USD550</p>

	<p>TM-TJ</p> 	<p><b>Class N</b></p> <ol style="list-style-type: none"> <li>1. Microcomputer display working status, touch buttons.</li> <li>2. Maximum temperature: up to 134 °C, suit for 4-6 minutes rapidly sterilizing.</li> <li>3. Safe protection of water lacking.</li> <li>4. With over-temperature, over-pressure auto-protect device:</li> <li>5. After sterilization it will automatically cut the power and then alarm.</li> <li>6. Fully stainless steel structure.</li> </ol>	<p>24L:USD715</p>
<p>Desktop Autoclave</p>	<p>TM-TD</p> 	<p><b>Class N, Computer control</b></p> <ol style="list-style-type: none"> <li>1. Sterilization automatic controlled by computer.</li> <li>2. Maximum temperature: up to 134 °C, suit for 4-6 minutes rapidly sterilizing.</li> <li>3. Water cutts off protection.</li> <li>4. Equipped with three stainless steel disinfection plate.</li> <li>5. With over-temperature, over-voltage automatic protection device.</li> <li>6. Automatically cut off the power and voice prompts after sterilization.</li> <li>7. Fully stainless steel structure.</li> </ol>	<p>24L:USD1050</p>

<p>Desktop Autoclave</p>	<p>TM-XBJ</p> 	<p><b>Class N</b></p> <ol style="list-style-type: none"> <li>Indicator light indicates working state.</li> <li>For 4~6 minutes rapidly sterilizing.</li> <li>Sterilizing temperature and time can be preset.</li> <li>Steam-water inner circulation system,no steam discharge.</li> <li>Over temperature &amp; over pressure auto-protection.</li> <li>Safe protection of water lacking.</li> <li>Exhaust the cool air automatically.</li> <li>With three stainless steel sterilizing plates.</li> <li>The chamber is made of stainless steel.</li> <li>Automatically shut off with beep reminding after sterilization.</li> </ol>	<p>20L:USD835 24L:USD1075</p>
	<p>TM-XAJ</p> 	<p><b>Class N</b></p> <ol style="list-style-type: none"> <li>Indicator light indicates working state.</li> <li>For 4~6 minutes rapidly sterilizing.</li> <li>Sterilizing temperature and time can be preset.</li> <li>Steam-water inner circulation system,no steam discharge.</li> <li>Over temperature &amp; over pressure auto-protection.</li> <li>Safe protection of water lacking.</li> <li>Exhaust the cool air automatically.</li> <li>Door safety lock system.</li> <li>With three stainless steel sterilizing plates.</li> <li>Automatically shut off with beep.</li> </ol>	<p>20L:USD1310 24L:USD1550</p>

<p>Desktop Autoclave</p>	<p>TM-XAD</p> 	<p><b>Class N,Computer control,With drying</b></p> <ol style="list-style-type: none"> <li>1.For 4~6 minutes rapidly sterilizing.</li> <li>2.Digital display,touch type key.</li> <li>3.With 3 fixed cycles of water adding,temperature rising,sterilizing,drying steam discharging controlled automatically.</li> <li>4.Steam-water inner circulation system,no steam discharge.</li> <li>5.Exhaust the cool air automatically.</li> <li>6.Safe protection of water lacking.</li> <li>7.Door safety lock system.</li> <li>8.With stainless steel cahmber and three stainlesssteel plates.</li> <li>9.Automatically shut off with beep</li> <li>10.With drying function.</li> </ol>	<p>20L:USD1910 24L:USD2150</p>
	<p>TM-XDJ</p> 	<p><b>Class N</b></p> <ol style="list-style-type: none"> <li>1.Indicator light indicates working state.</li> <li>2.For 4~6 minutes rapidly sterilizing.</li> <li>3.Temperature and time can be preset.</li> <li>4.Steam-water inner circulation system,no steam discharge.</li> <li>5.Over temperature and over pressure auto-protection can be realized.</li> <li>6.Safe protection of water lacking.</li> <li>7.Exhaust the cool air automatically.</li> <li>8.Door safety lock system.</li> <li>9.With stainless steel cahmber and three stainlesssteel plates.</li> <li>11.Automatically shut off with beep reminding after sterilization.</li> </ol>	<p>35L:USD2145 50L:USD2740</p>

<p>Desktop Autoclave</p>	<p>TM-XDD</p> 	<p><b>Class N,Computer control,With drying</b></p> <ol style="list-style-type: none"> <li>1.For 4~6 minutes rapidly sterilizing.</li> <li>2.Digital display of working status,touch type key.</li> <li>3.With 3 fixed cycles of water adding,temperature rising,sterilizing,drying steam discharging controlled automatically.</li> <li>4.The whole process of water adding,temperature rising,sterilizing,drying steam discharging controlled automatically.</li> <li>4.Steam-water inner circulation system:no steam discharge,and the environment for sterilizing will be clean and dry.</li> <li>5.Exhaust the cool air automatically.</li> <li>6.Safe protection of water lacking.</li> <li>7.Door safety lock system.</li> <li>8.With four stainless steel sterilizing plates.</li> <li>9.The chamber of the sterilizer is made of stainless steel.</li> <li>10.Automatically shut off with beep reminding after sterilization.</li> <li>11.With drying function.</li> </ol>	<p>35L:USD2620 50L:USD3220</p>
--------------------------	---	--	------------------------------------

<p>Desktop Autoclave</p>	<p>TM-XDV</p> 	<p><b>Class B,With vacuum drying</b></p> <ol style="list-style-type: none"> <li>1.Standard Class B with three times vacuum and drying, the remaining temperature of sterilized instrument is less than 0.2%.</li> <li>2.LCD display working status, touch keys.</li> <li>3.The vacuum data can reach-0.8bar,it fits various instrument,including package,unpacked,solid,hollow,multi—apertures and inset pipes It makes sum the instrument can be sterilized completely.</li> <li>4.Fully computer controlled LCD display bright show The interface is modularized panel for easy operation.</li> <li>5.It is installed with BOWIE&amp;DICK which measures the penetration of water steam.</li> <li>6.it has vacuum text which can make sure the ability of texting vacuuming.</li> <li>7.Fast and independent steam generator</li> <li>8.Built—in mini printer which can record the sterilizer information.</li> <li>9.Safety valve,Safety lock door system,Pressure lock system,Pressure or temperature overload protection,Alarm system.</li> <li>10.Can inactivate HIV,HBV, mad COW Virus and bacillus.</li> </ol>	<p>20L:USD2150 24L:USD2700 35L:USD3200 50L:USD4080</p>
--------------------------	--	--	--

	<p>LS-LJ</p> 	<p><b>Flip-up cover, Timing, Temp. Control, Water automatic cuts off, double baskets.</b></p> <ol style="list-style-type: none"> <li>1. Fully stainless steel structure</li> <li>2. Indicator light indicates working state</li> <li>3. Over temperature &amp; over pressure auto-protection</li> <li>4. Double scale indication pressure gauge</li> <li>5. Safe protection of water lacking</li> <li>6. Automatically shut off with beep reminding after sterilization</li> <li>7. Easy to operate, safe and reliable</li> <li>8. With two stainless steel sterilizing baskets</li> </ol>	<p>35L: USD750 50L: USD1050 75L: USD1400 100L: USD1900 120L: 2290 150L: 2630</p>
<p>Vertical Autoclave</p>	<p>LS-LD</p> 	<p><b>Flip-up cover, Digital display, Auto discharge cool air, Water automatic cuts off, Auto discharge steam, double baskets.</b></p> <ol style="list-style-type: none"> <li>1. Fully stainless steel structure.</li> <li>2. Digital display of working status, touch type key.</li> <li>3. Auto discharge the cool air, and steam discharging automatically after sterilization.</li> <li>4. Automatically shut off with beep.</li> <li>5. Easy to operate, safe and reliable</li> <li>6. With two stainless steel sterilizing baskets.</li> <li>7. The drying system is optional, which can be equipped according to the customers request.</li> </ol>	<p>35L: USD810 50L: USD1120 75L: USD1460 100L: USD2000</p>

<p>Vertical Autoclave</p>	<p>LS-HJ</p> 	<p><b>Hand wheel door, Timing, Temp. Control, Water automatic cuts off, double baskets.</b></p> <ol style="list-style-type: none"> <li>1. Fully stainless steel structure.</li> <li>2. Hand wheel quick-open door structure.</li> <li>3. Pressure safety lock.</li> <li>4. Indicator light indicates working state.</li> <li>5. Over temperature &amp; over pressure auto-protection.</li> <li>6. Double scale indication pressure gauge.</li> <li>7. Self-inflating type seal.</li> <li>8. Safe protection of water lacking.</li> <li>9. Automatically shut off with beep beep.</li> <li>10. With two stainless steel sterilizing baskets.</li> </ol>	<p>35L:USD960 50L:USD1270 75L:USD1560 100L:USD2050 120L:2440 150L:2780</p>
<p>Vertical Autoclave</p>	<p>LS-HD</p> 	<p><b>Hand wheel door, Digital display, Auto discharge cool air, Water automatic cuts off, Auto discharge steam, double baskets.</b></p> <ol style="list-style-type: none"> <li>1. Fully stainless steel structure.</li> <li>2. Hand wheel quick-open door structure.</li> <li>3. Door safety lock system.</li> <li>4. Digital display, touch of key.</li> <li>5. Auto discharge the cool air and steam.</li> <li>6. Over temperature &amp; over pressure auto-protection.</li> <li>7. Safe protection of water lacking.</li> <li>8. Self-inflating type seal.</li> <li>9. Automatically shut off with beep.</li> <li>10. Possible to install drying system according request.</li> </ol>	<p>28L:USD850 35L:USD1000 50L:USD1350 75L:USD1660 100L:USD2150</p>

	<p>LS-HG</p> 	<p><b>Full automatic computer controlled ,LCD Display, Automatic moisturizing, Steam and water inner circulating, without discharge steam outside.</b></p> <ol style="list-style-type: none"> <li>1. Fully stainless steel structure.</li> <li>2. Hand wheel quick-open door structure.</li> <li>3. Door safety lock system.</li> <li>4. Automatically controlled by computer.</li> <li>5. Digital display, touch of key.</li> <li>6. Over temperature &amp; over pressure auto-protection.</li> <li>7. Steam-water inner circulation system, no steam discharge.</li> <li>8. Self-inflating type seal.</li> <li>9. Safe protection of water lacking.</li> <li>10. Possible to install drying system according request.</li> <li>11. Automatically shut off with beep.</li> <li>12. With two stainless steel baskets.</li> </ol>	<p>35L:USD1660 50L:USD2190 75L:USD2880 100L:USD3590</p>
	<p>LS-HV</p> 	<p><b>Pulsating vacuum, LCD, With vacuum drying.</b></p> <ol style="list-style-type: none"> <li>1. The chamber of the sterilizer is made of stainless steel.</li> <li>2. Indicator light indicates working state.</li> <li>3. Over temperature &amp; over pressure auto-protection.</li> <li>4. Safe protection of water lacking.</li> <li>5. Double scale indication pressure gauge.</li> <li>6. Automatically shut off with beep.</li> <li>7. With two stainless steel sterilizing baskets.</li> </ol>	<p>35L:USD2730 50L:USD3410 75L:USD4180 100L:USD5150</p>

<p>Horizontal Autoclave</p>	<p>WS-YDA</p> 	<p><b>Stainless steel inner chamber,Full automatic</b></p> <ol style="list-style-type: none"> <li>1. Sterilizing course automatic sterilization controlled,easy to operate.</li> <li>2. With drying function,suitable dressing drying.</li> <li>3. With over-temperature,over-pressure auto-protect device.</li> <li>4. The door opening mechanism cannot be operated until the pressure in the chamber is reduced to 0.027MPa.It can't be start on if the door doesn't close well.</li> <li>5.The safety value will be open automatically when the inner pressure over 0.24MPa,and the steam be exhausting to the water tank.</li> <li>6. The power will be cut-off automatically,cut-off the water and alarm when the machine lacking water.</li> <li>7. The chamber of the sterilizer is made of stainless steel.</li> </ol>	<p>150L:USD3900 200L:USD4300 280L:USD4800 400L:USD6500 500L:USD8100</p>
-----------------------------	--	---	---

<p>Horizontal Autoclave</p>	<p>WS-YDB</p> 	<p><b>Stainless steel inner chamber,With printer</b></p> <ol style="list-style-type: none"> <li>1.Sterilizing course automatic sterilization controlled by computer, easy to operate.</li> <li>2.With drying function, suitable dressing drying.</li> <li>3.With over-temperature, over-pressure auto-protect device.</li> <li>4.The door opening mechanism cannot be operated until the pressure in the chamber is reduced to 0.027MPa.It can't be start on if the doesn't closed well.</li> <li>5.The safety value will be open automatically when the inner pressure over 0.24MPa, and the steam be exhausting to the water tank.</li> <li>6.The power will be cut-off automatically, cut-off the water and alarm when the machine lacking water.</li> <li>7.The chamber of the sterilizer is made of stainless steel.</li> <li>8.With printer.</li> </ol>	<p>150L:USD4800 200L:USD5700 280L:USD6800</p>
-----------------------------	---	---	---

<p>Horizontal Autoclave</p>	<p>WS-YDC</p> 	<p><b>Full stainless steel,Full automatic</b></p> <ol style="list-style-type: none"> <li>1. Sterilizing course automatic sterilization controlled,easy to operate.</li> <li>2. With drying function,suitable dressing drying.</li> <li>3. With over-temperature,over-pressure auto-protect device.</li> <li>4. The door opening mechanism cannot be operated until the pressure in the chamber is reduced to 0.027MPa.It can't be start on if the door doesn't close well.</li> <li>5.The safety value will be open automatically when the inner pressure over 0.24MPa,and the steam be exhausting to the water tank.</li> <li>6. The power will be cut-off automatically,cut-off the water and alarm when the machine lacking water.</li> <li>7. Fully stainless steel structure.</li> </ol>	<p>150L:USD6800 200L:USD7800 280L:USD11700</p>
-----------------------------	--	---	--

<p>Horizontal Autoclave</p>	<p>WS-YDD</p> 	<p><b>Full stainless steel,With printer</b></p> <ol style="list-style-type: none"> <li>1.Sterilizing course automatic sterilization controlled by computer, easy to operate.</li> <li>2.With drying function, suitable dressing drying.</li> <li>3.With over-temperature, over-pressure auto-protect device.</li> <li>4.The door opening mechanism cannot be operated until the pressure in the chamber is reduced to 0.027MPa.It can't be start on if the doesn't closed well.</li> <li>5.The safety valve will be open automatically when the inner pressure over 0.24MPa, and the steam be exhausting to the water tank.</li> <li>6.The power will be cut-off automatically, cut-off the water and alarm when the machine lacking water.</li> <li>7.The chamber of the sterilizer is made of stainless steel.</li> <li>8.With printer.</li> </ol>	<p>280LUSD:12000</p>
-----------------------------	--	--	----------------------