




SPECIFICATIONS

- Voltage rating: 500V AC,DC
- Current rating: 3A AC,DC
- Withstanding Voltage: 1000V AC/minute
- Insulation resistance: 500MΩ min
- Temperature range: -40°C~+105°C

WAFER

- Part NO: AW2512V-S-xP
- Material: Pin: Brass/Tin over Nickel
Insulator: Nylon 66, UL94V-0
- Mates with: AH2512 series Housing
- Color: Ivory



Ordering Information & Dimensions:

PART NO.	Dimensions	
	A	B
AW2512V-S-2P	2.50	10.00
AW2512V-S-3P	5.00	12.50
AW2512V-S-4P	7.50	15.00
AW2512V-S-5P	10.00	17.50
AW2512V-S-6P	12.50	20.00
AW2512V-S-7P	15.00	22.50
AW2512V-S-8P	17.50	25.00
AW2512V-S-9P	20.00	27.50
AW2512V-S-10P	22.50	30.00
AW2512V-S-11P	25.00	32.50
AW2512V-S-12P	27.50	35.00
AW2512V-S-13P	30.00	37.50
AW2512V-S-14P	32.50	40.00
AW2512V-S-15P	35.00	42.50
AW2512V-S-16P	37.50	45.00

Unit: mm

Unless Otherwise specified tolerance

X. ±0.35 X.XX: ±0.20
 X.X: ±0.25 X.XXX: ±0.15


SCALE: UNIT:
 As Shown mm

DRAW DATE
 Jack Bao 5/14/2018

CHECK DATE
 Bob Yang 5/14/2018

Antenk® ANTENK ELECTRONICS CO.,LTD
[Http://www.antenk.com](http://www.antenk.com)
 E-mail:sales@antenk.com

TITLE: 2.50mm pitch 180° Wafer SMT-TYPE
 Connector Series



DRAWING NO: AW2512V-S-xP

PRODUCT NO: AW2512V-S-xP

Update: AH2512V-S-XP -> AW2512V-S-XP

05/04/2024

DESCRIPTION

DATE



REV