

Recommended P.C.B. Layout  
NEW DWG  
DESCRIPTION

SPECIFICATION

Current Rating: 5.6Amp  
 Insulation Resistance: 1000MΩ min. at DC 500V  
 Contact Resistance: 20mΩ max  
 Withstand Voltage: AC 1000V For 1 Minute  
 Operating Temperature: -55° C to +105° C  
 Contact Material: Phosphor Brass  
 Contact Plating: Au or Sn Over Ni  
 Insulator Material: PBT+30%GF UL 94V-0  
 Insertion Force: 75N max.  
 Withdrawal Force: 0.15N min. per individual contact

Ordering Code:

DMR - X - X - X - X - D06  
 ① ② ③ ④ ⑤ ⑥


- ① Series No:
- ② No. of Contacts  
48P 32P
- ③ Termination  
B: Right angle tail length H=3.0mm
- ④ Rows Loaded With Contacts  
G: Row d+b+z  
I: Row d+z
- ⑤ Contact Plating  
G0: Gold flash  
S0: Gold flash/Ni  
G1: 3u" Gold  
G2: 5u" Gold  
S1: 3u" Gold/Ni  
G3: 5u" Gold  
S2: 5u" Gold/Ni  
G4: 10u" Gold  
S3: 10u" Gold/Ni  
G5: 15u" Gold  
S4: 15u" Gold/Ni  
G6: 30u" Gold  
S5: 30u" Gold/Ni  
SN: Tin

Code	Number Of Contacts	Contact Arrangement	Rows With Contacts	Pitch
G	48		d b z	5.08
I	32		d z	

⑥ Series number D06

Unless Otherwise specified tolerance  
 X. ±0.35 X.XX: ±0.20  
 X.X: ±0.25 X.XXX: ±0.15

SCALE: As Shown UNIT: mm  
 DRAW Wu Feng Rong DATE 23/11/2019  
 CHECK BobYang DATE 23/11/2019



**Antenk** ANTENK ELECTRONICS CO., LTD  
 Http://www.antenk.com  
 E-mail: sales@antenk.com

TITLE:  
 DIN41612 Right Plug F Type High Power  
 Connectors 48 Positions (Terminal Width=1.54MM)

DRAWING NO: DMR-XX-XXX-D06

PRODUCT NO: DMR-XX-XXX-D06

REV	DESCRIPTION	DATE