





HSF



ROHS



PC Board Layout
Component Side Shown

NOTES:

MATERIAL:

1. HOUSING MATERIAL: GLASS FILLED POYESTER UL94V-0.
2. CONTACT MATERIAL: PHOSPHOR BRONZE $t=0.3\text{mm}$
3. PLATING: SELECTING GOLD PLATING $1\mu\sim 50\mu$ "OVER NICKEL IN CONTACT AREA. 150μ " TIN PLATIN. OVER NICKEL IN SOLDER AREA
4. SHIELD: 0.2mm THICKNESS COPPER WITH NICKEL PLATE

ELECTRICAL

1. VOLTAGE RATING: 125V AC RMS
2. CURRENT RATING: 1.5AMP
3. CONTACT RESISTANCE: 30 MILLIOHMS MAX
4. INSULATION RESISTANCE 500 MEGOHMS MIN @500V DC
5. DIELECTRIC WITHSTANDING RESISTANCE : 1000V AC RMS 50Hz. 1MIN

MECHANICAL

1. DURRABILITY: 750 CYCLES MIN
2. PCB RETENTTON PRB-SOLDER: 1 LB MIN

REVRONMENTAL

1. STORAGE: -40° C TO 85° C
2. OPERATION: 0° C TO 70° C

Order code:

ATRJ5921 - 10P - 8C - X - D - A - C
① ② ③ ④ ⑤ ⑥ ⑦

① SERIES NO:

② NUMBER OF POSITIONS (10P, 8P, 6P, 4P)

③ NUMBER OF CONTACTS (10C, 8C, 6C, 4C)

④ Contact Plating

G0: Gold flash

G1: 3U" Gold

G2: 5U" Gold

G3: 10U" Gold

G4: 15U" Gold

G5: 30U" Gold

SN: Tin

⑤ Shield

A: W/O Shield

B: Half Shield

C: Shield W/Eml

D: Shield W/O Eml

⑥ Ports

A: 1X1P G: 2X1P

B: 1X2P H: 2X2P

C: 1X4P I: 2X3P

D: 1X5P J: 2X4P

E: 1X6P K: 2X6P

F: 1X8P L: 2X8P

⑦ PCB layout style:

A: TYPE 1 front legs 3.05

B: TYPE 1 front legs 3.68

C: TYPE 1 front legs 4.57

D: TYPE 2 Back legs 3.05

E: TYPE 2 Back legs 3.68

F: TYPE 2 Back legs 4.57


Unless Otherwise specified tolerance

X. ± 0.35 X.XX: ± 0.20
X.X: ± 0.25 X.XXX: ± 0.15

SCALE: As Shown UNIT: mm

DRAW Wu Feng Rong DATE 22/03/2018

CHECK BobYang DATE 22/03/2018



ANTENK ELECTRONICS CO., LTD

Http://www.antenk.com

E-mail: sales@antenk.com

TITLE:

RJ45 Jack side entry, shielded,
1X8P Front 4.57

DRAWING NO:

ATRJ5921-10P8C-X-D-A-C

PRODUCT NO:

ATRJ5921-10P8C-X-D-A-C

REV

DESCRIPTION

DATE

1

2

3

4

5

6

7

8