

## **Benefits**

- 1. Replace conventional Highbay Lights.
- 2. Precision Die Cast Aluminum Housing.
- 3. Fade Resistant Powder Coat Finish.
- 4. Easy Installation.
- 5. Without power supply,IC driver, single voltage 120V,240V,277V.
- 6. CE ROHS listed.







100W 150W 200W



#### **Features**

- 1. Beam angle:60 90 110 degrees.
- 2. Aluminum die-casting heat sinks is good for heat dissipation.
- 3. It's major to replace the conventiona highbay light.
- 4. Green, energy saving, long and reliable life of 50,000 hours.
- 5. No RF interference, No IR/UV radiation, no mercury pollution.
- 6. Wide colour availability in degrees Kelvin(K),2700-6700K.
- 7. Streamline exterior design, beautiful appearance.
- 8. Environment friendly, energy saving (70~80%).
- 9. Special circuit design, each LED work separately, avoiding the single broken LED influence problem.









#### **Application**

- 1. Parking areas Lighting.
- 2. Ceiling Lighting.
- 3. Warehouse Lighting.
- 4. High/Low Bay Lighting.









# SPECIFICATIONS

Power	100W	150W	200W			
Model	BB-GKD-100W-E5	BB-GKD-150W-E5	BB-GKD-200W-E5			
Luminous Flux	13000lm	19500lm	26000lm			
Replacement	HPS 300W	HPS 450W	HPS 600W			
Model differences	Different installation accessories: A-Ring mounting; B-Bracket mounting					
Light Sourse	SMD LED					
Luminous Efficacy	130lm/W					
Operation Temp.	-40 to +45℃					
ССТ	2700K SW / 3000K WW / 4100K NW / 5000K DW / 5700K CW / 6500K SCW					
CRI	85					
Life Span	50,000 hours at 25°C					
Voltage	Single voltage 120V, 240V,277V,optional					
Driver	Without power supply,IC Driver					
Dimming	No					
Sensor	Microwave sensor, optional.					
Control System	APP, remote control, touch screen, light control and other control options available					
Beam Angle	60° 90° 110°					
Cover	Lens or Glass, optional.					
IP	65					
PF	>0.95					
Warranty	5Years					

# **DIMENSIONAL DRAWING**



## **LUMINOUS INTENSITY DISTRIBUTION**



#### **PROJECTS**

By using our 100W Highbay Light to replace 300W Metal Halide bulb for warehouse high bay lighting fixtures, the customer is now able to save a lot per month from his electric bill.




100W LED = 300W MH


#### Note:

- Don't take the LED lamp apart.
- The LED lamp must work under the right voltage according to the specification.


# INSTALLATION

UFO LED Highbay Light has four kinds of installation:





2.Bracket type



### **PACKING INFO**



Packaging	Carton Size(mm) (L*W*H)	N.W	G.W	Volume weight
1pc/CTN(100W)	320*320*165mm	1.7kg	2.5kg	4.28kg
1pc/CTN(150W)	355*350*165mm	2.2kg	3.0kg	5.14kg
1pc/CTN(200W)	410*410*175mm	3.3kg	4.0kg	7.21kg