



QN8003 Technical Parameters

System Configuration

processor	M3 32-bit processor
Flash	2048Kb RAM
ROM	4MB
Display screen	0.96inch OLED
button	Switch on / Set / Feed
battery	Removable 7.4v 1400mAh High Performance Lithium Battery
Power Adapter	Input AC 110-200V, input DC 9V/1.5A
Size (LxWxD)	109mmX104mmX48.5mm
weight	345g

support system	Android/IOS/Windows/Symbian/Win CE
Paper type	Ordinary thermal paper/heat-sensitive label paper
Roll diameter	Maximum Φ 39mm

Use environment

storage temperature	-20°- 70°C
humidity	0 ~ 95% (No condensation)

Communications

Bluetooth	Bluetooth 2.0/4.0
USB	USB2.0

Printing parameters

printing method	Line thermal printing
Print width	72mm (24 characters/line 48 English characters/line or standard 24 dot matrix font)
printing speed	80mm/s max
Character Encoding	Codepage, Unicode,UTF-8
Built-in font	ASCII font (8x16, 12x24, 16x32, 24x48, 32x64) GB13080(16 x16,24 x24,68 x48)
Print instruction	TSPL tag instruction POS/ESC instruction
sensor	Double black mark / paperless / low power
Error warning	Out of paper/paper bin door open/low power
Error message	Buzzer/OLED display tips
System language	Chinese-English



Shenzhen Qunso Technology Co., Ltd.

4th Floor, Building C, Fu xin lin Industrial Park, Xi xiang Street, Bao`an District, Shenzhen

0755-61153535 <http://www.szqunsuo.com> info@szqunsuo.com