

• "Design for simple and convenience" the idea

Shenzhen GreenTouch Technology Co., Ltd. is a professional manufacturer of product.Our company specializes in R&D, manufacture and marketing of high-grade

brand—GreenTouch and provides customers with touch products including SAW touch screen, IR touch screen, four-wire touch screen, five-wire touch screen, vari-

production lines and the sealed dust-free workshops and has been certified to

ISO9001 Quality Management System . The products are inspected in strict

ous touch screen monitors and touch all in one PC TV. GreenTouch has automatic

accordance with the quality management system. Quality management becomes an

essential part of operation.Our products have been certified to CE, FCC, ROHS . The

objective of GreenTouch is to become the most reliable supplier oftouch screen,

high value-added and special touch products and touch solutions in the world.

touch screen and value-added touch machine. Our company has our own

Outstanding quality, reliability and Cost-effective

# 2203A 22" LCD Android touch all-in-one

**Features** 

 Optional Motherboard Configuration inlcudes: ZC-3566

Stylish appearance

· Easy integration, low maintenance

Drift free operation

GreenTouch's 3A series Android touch all-in-one PCs are touch solutions with low power consumption, ultra-thin body design, high-resolution display and excellent multi-touch interactive experience. Compared with ordinary monitors. 3A series of professional design and High performance is more suitable for applications in retail and other industries. Designed and built by GreenTouch, this model has a long life cycle and can supply long-term needs.

This model is versatile and powerful, with modular design and optional configuration. For customers with low performance requirements, it is recommended to choose the ultra-low power consumption and cost-effective ZC-3566 solution: the board integrates multimedia decoding. LCD driver, Ethernet, HDMI, WIFI, 3G, Bluetooth, supports most of the current popular video and picture format decoding, supports HDMI video output, TF card , which greatly simplifies the system design of the whole machine; built-in speaker, 12V low-voltage power supply.

The all-in-one machine comes with a series of output connection ports, supporting various third-party peripheral devices. Standard ports include 2 standard USB ports, a 100 megabit wired network card interface, and 1 3.5MM audio left and right channel output, 1 TF card, and 1 HDMI video output port, making it easy to add a second customer display.

The series features industry-leading GreenTouch projected capacitive touch technology. This model has global regulatory agency certification, as well as GreenTouch's warranty and after-sales service. It provides a cost-effective all-in-one touch solution for industrial embedded system integrators and value-added resellers (VARs).





#### retail terminal Rail transit · Finance and other industries self service

Applications

About GreenTouch

# **Specifications**

| Case/ frame color                         | Black  |  |  |  |
|---|--|--|--|--|
| Machine dimensions                        | 524.1mm(W) x346.5 mm(H),Thickness:42 mm  |  |  |  |
| Display type                              | 22'Diagonal,Ratio16:10,Active matrix TFT LCD, LED backlight  |  |  |  |
| Resolution(pixel)                         | 1680 x 1050 @ 60Hz   |  |  |  |
| Active Area Dimensions                    | 475.7mm(H) x 298.1mm(V)  |  |  |  |
| Display Colors                            | 16.7M  |  |  |  |
| Brightness (Standard)                     | 250 cd/m <sup>2</sup>  |  |  |  |
| Response time (standard)                  | 3.7ms  |  |  |  |
| View Angle(from center)                   | Horizontal (left / right): ±85° or a total of 170°<br>Vertical (up / down): ± 80° or a total of 160°   |  |  |  |
| Contrast ratio (standard)                 | 1000: 1(Typ.)  |  |  |  |
| Touch Technology                          | projected capacitive<br>Touch chip: weida<br>Touch points: 1-10<br>Touch supply voitage: SV<br>Touch interface: USB<br>Touch support system: Vindows, Android, linux   |  |  |  |
| Motherboard                               | ZC-3566<br>Rockchip RK3566 High-performance, low-power quad-core 64-bit Cortex-A55, the main frequency i:<br>up to 1.8Ghz  |  |  |  |
| Operating system                          | Android  |  |  |  |
| Memory                                    | DDR3 4GB   |  |  |  |
| Built in memory                           | EMMC FLASH 32G   |  |  |  |
| Network support                           | 3G、 Ethernet, WiFi / Bluetooth 4.0, wireless peripheral extension  |  |  |  |
| Wireless                                  | Built in WiFi or WiFi / BT module (optional), 802.11b/g/n, default single WiFi module, external 1<br>3dB omnidirectional antenna   |  |  |  |
| Speakers                                  | Built-in 2*2W speakers   |  |  |  |
| HDMI Output                               | 1, Support 1080P@120Hz,4kX2k@60Hz Output   |  |  |  |
| USB interface                             | 2 xUSB HOST  |  |  |  |
| TF Card                                   | Support TF Card  |  |  |  |
| Headset / Microphone                      | 1 external headphone audio output  |  |  |  |
| Audio and video output                    | Support left and right channel output, built-in 8R / 2W power amplifier  |  |  |  |
| Video function                            | USB camera support   |  |  |  |
| Power                                     | Extemal DC, input voltage DC: 12V; INPUT POWER CONNECTOR SPECIFICATIONS (for all in one P<br>Type: DC cartifige receptade; Cartifige ID: 5.5 mm<br>(± 0.3 mm); Needle OD: 2.0 mm (+0.0 -0.1 mm); Cartifige depth: 8.0 mm (± 0.3 mm); |  |  |  |
| Power consumption (standard)              | Depend on Motherboard and the minimum is 25W   |  |  |  |
| Temperature                               | Operating: 0°Cto 50°C; Storage: -20°C to 60°C  |  |  |  |
| Humidity                                  | Operating: 20% to 80% (non-condensing); Storage: 5% to 95% (non-condensing)  |  |  |  |
| Warranty                                  | 1 year   |  |  |  |
| Weight (approx.)                          | Net weight: 7 kg(Typ.); Shipping: 8.8 kg (reference)   |  |  |  |
| Mounting options                          | 100mm or 75mm VESA mounting  |  |  |  |
| Water and dust protection/Explosion-proof | IP65(front)/IK06(front)  |  |  |  |
| Surface treatment                         | NA   |  |  |  |
| Agency Approvals                          | FCC, CE, CB, China RoHS CQC  |  |  |  |

## Ordering Information

| Model                      | CPU    | RAM | Storage | Surface Treatment | Availability |
|----------------------------|--------|-----|---------|-------------------|--------------|
| GT-TC3A-220-RK3566-D4GS32G | RK3566 | 4G  | 32G     | Clear             | Worldwide    |

To find out more about our extensive range of GreenTouch touch solutions, go to www.greentouch.com.cn, or ifo@greentouch.com.cn

### Service call:+86-755-29370883/29371519

Shenzhen GreenTouch Technology Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. GreenTouch (logo) and Shenzhen GreenTouch Technology Co., Ltd. Copyright . All rights reserved 2016 Shenzhen GreenTouch Technology Co., Ltd. All rights reserved.