

XN800


MINI DUMPER











KOOP ENGINE SPECIFICATION			XN800-Briggs&Stratton B420 SPECIFICATION		
Operating weight		630kg	Operating weight		745kg
Capacity of loading		800kg	Capacity of loading		800kg
Bucket capacity		0.26m ³	Bucket capacity		0.26m ³
Working type		Self loading and unloading	Working type		Self loading and unloading
Engine	Brand	Koop192	Engine	Brand	Briggs&Stratton420
	Displacement	0.499L		Displacement	0.420L
	Rated power/Rev	7.6 Kw/3000rpm		Rated power/Rev	9.9Kw/3600r/min
	Max. Torque	23.8N.m/3000rpm		Max. Torque	26N.m/2860r/min
Speed	Max. speed	4.2km/h	Speed	Max. speed	4km/h
	Min. speed	2.1km/h		Min. speed	2km/h
	Max. gradeability	30%		Max. gradeability	30%
Track	Ground pressure	21.21KPa	Track	Ground pressure	21.21KPa
	Material	Rubber		Material	Rubber
	Tightening type	Screw adjustment		Tightening type	Screw adjustment
Hydraulic system	Pump type	Gear Duplex Pump	Hydraulic system	Pump type	Gear Duplex Pump
	Pressure	16MPa		Pressure	16MPa
	Flow	30L/min		Flow	30L/min
Tank capacity	Hydraulic oil tank	12.8 L	Tank capacity	Hydraulic oil tank	14 L
	Fuel tank	5.5L		Fuel tank	6.6L

KUBOTA ENGINE SPECIFICATION						
Operating	weight	860kg				
Capacity of	of loading	800kg				
Bucket capacity		0.26m ³				
Working type		Self loading and unloading				
	Brand	KUBOTA D722				
Facility	Displacement	0.719L				
Engine	Rated power/Rev	10.2Kw/2500r/min				
	Max. Torque	42.9N.m/2000r/min				
	Max. speed	4 km/h				
Speed	Min. speed	2 km/h				
	Max. gradeability	30%				
	Ground pressure	26.13KPa				
Track	Material	Rubber				
	Tightening type	Screw adjustment				
	Pump type	Gear Duplex Pump				
Hydraulic svstem	Pressure	16MPa				
_,	Flow	30L/min				
Tank	Hydraulic oil tank	14L				
capacity	Fuel tank	16L				

MAIN DIMENSION	
a Track width	914mm
b Track length	1230mm
c Length	1795mm
d Track height	320mm
e Height of tip front end from ground	810mm
f Height from self loading bucket to ground	1690mm
g Platform off ground	355mm
h Control console height above ground	1005mm
i Height of tip back from ground	1060mm
j Width	820mm
k Track width	180mm
m Tipping bucket width	620mm
n Maximum Dumping Height	1700mm
P Maximum unloading tipper height	2980mm







