



Characteristics

- ★ Extended Operating Temperature Range: Greensaver batteries are able to operate under the harshest environments from -40°C-+60°C temperatures
- ★ Maintains High Capacity Under Low Temperatures: Greensaver Batteries are able to hold 80-85% of their total capacity under-10°C temperatures.
- ★ High Charge Acceptance Ability: With low internal resistance, Greensaver batteries have high charge efficiency and have fast charging ability.
- ★ Long Battery Life: Without electrolyte stratification using patented electrolyte, Greensaver batteries have cycle life more than 1200 cycles.

Applications

- ★ Golf cart, wheelchairs, Sweepers, Marine systems;
- ★ Electric car, Electric bike.
- ★ Solar energy and wind energy systems;
- ★ Power station system;

Nominal Voltage		12V
Nominal Capacity (20 hour rate)		26 Ah
Capacity 25°C (77°F)	10 hour rate	25.2Ah
	5 hour rate	22.8 Ah
	2 hour rate	22 Ah
Internal Resistance	Full Charged Battery 25°C	≤15m Ω
Capacity affected by Temperature (10 hour)	40°C (104°F)	102%
	25°C (77°F)	100%
	0°C (32°F)	90%
	-15°C (5°F)	80%
Self-Discharge 25°C (77°F) Capacity	after 3 month storage	95%
	after 6 month storage	85%
	after 12 month storage	80%
Charge (Constant Voltage) 25°C (77°F)	Float	Initial Charging Current Less than 5 A Voltage 13.6-13.8V
	Cycle	Initial Charging Current Less than 5 A Voltage 14.4-14.9V

Battery Dimensions	Length	180 mm
	Width	76 mm
	Height	170 mm
	Total Height	181 mm
Box Dimensions	Length	---mm
	Width	---mm
	Height	--mm
Quantity Per Box		--PC per box
Net weight Per Cell		6.8kg±100g
Net weight Per Box		----kg
Gross Weight		----kg

Discharge Constant Current per Cell (Amperes at 77°F25°C)


F.V/Time	5min	10min	15min	30min	45min	1h	2h	3h	5h	8h	10h	20h
1.60V	87.4	58.2	43.9	27.3	19.6	17.3	10.5	7.7	5.0	3.0	2.70	1.50
1.65V	80.6	53.7	42.1	26.6	19.1	16.8	10.3	7.6	4.9	3.0	2.68	1.49
1.70V	82.0	54.6	40.2	25.9	18.5	16.4	10.2	7.4	4.8	3.0	2.65	1.47
1.75V	72.4	48.2	38.4	25.1	18.0	15.9	9.9	7.2	4.8	2.9	2.63	1.46
1.80V	68.3	45.5	36.6	24.4	17.5	15.4	9.7	7.1	4.7	2.9	2.60	1.44

Discharge Constant Power per Cell (Watts at 77°F 25°C)


F.V/Time	5min	10min	15min	30min	45min	1h	2h	3h	5h	8h	10h	20h
1.60V	163.1	108.6	81.9	50.9	36.5	32.3	19.7	14.4	9.3	5.6	5.0	2.8
1.65V	150.3	100.1	78.5	49.6	35.6	31.4	19.3	14.1	9.1	5.6	5.0	2.8
1.70V	152.9	101.8	75.0	48.2	34.6	30.5	18.9	13.8	9.0	5.5	4.9	2.7
1.75V	135.0	89.9	71.6	46.8	33.6	29.7	18.5	13.5	8.9	5.5	4.9	2.7
1.80V	127.4	84.9	68.2	45.5	32.6	28.8	18.0	13.2	8.7	5.4	4.8	2.7

Performance Characteristic


放电深度与循环寿命的关系 (25°C)
Cycle life curves (25°C)



充电特性 Charge characteristics 77°F(25°C)



放电特性 Discharge characteristics 77°F(25°C)



不同温度下的放电容量

Temperature and discharge capacity

