

NS-2920

全自動洗衣染色機

Automatic Garment Washing and Dyeing Machine



NS-2920-500

- 適用於棉、毛、麻、化纖等衣物洗滌、染色，效果佳
- 採用PLC可編程控制器控制及人性化操作界面觸摸顯示屏操作
- 循環運水配合過濾系統，有效利用水資源
- 採用蒸汽直接加熱和外置式間接加熱系統，即時/到溫計時選擇
- SUS 304不鏽鋼內膽，可滿足不同染色及洗滌需求
- 採用變頻器控制，洗衣染色轉速可調
- 備兩個氣動入水和一個氣動排水，方便操作
- 氣動剎車裝置，停機後內門對外門自動控制

- Suitable for washing and dyeing of garments of cotton, wool, linen, synthetic fiber, etc. with superb effect
- Adopt PLC and user friendly touch screen for operation
- Effective use of water due to water circulating and filtering system
- Combination of direct steam heating and external indirect heating; use can choose immediate timing or reach-temperature timing mode
- SUS304 inner drum can satisfy different washing or dyeing requirements
- Inverter controlled continuous speed variation
- With two pneumatic water feeding systems and one pneumatic draining system to facilitate operation
- Pneumatic braking device enables automatic alignment of inner and outer doors after running

選購件:

NS-2291 藥水配量缸

Option:

NS-2291 chemical dosing tank

型號 Model	電源 Power Supply	容量(磅) Capacity (LBS)	內膽尺寸(mm) Inner Drum Size	外膽尺寸(mm) Outer Drum Size	外膽門 Outer Drum Door	馬達(kW) Motor	耗蒸汽量(kg/h) Steam Consumption	入水口 Water Inlet	出水口 Water Outlet	水容量(L) Water Capacity	轉速 Speed (RPM)	機器尺寸(mm) Machine Size
NS-2920-200	3PH/380V/50Hz	200	Ø1100x1090x3	Ø1250x1270x1.5	單門 Single door	4	80	Ø2"x1	Ø6"x1	744	30~33	2120x1730x1765
NS-2920-500		500	Ø1220x2260x4	Ø1370x2440x2	雙門 Double door	13.2	200	Ø3"x2	Ø8"x1	1735	8-36	3240x2100x2200
NS-2920-650		650	Ø1370x2260x4	Ø1500x2440x2			260			2244		3240x1950x2030



藝誠(余氏)發展有限公司
Ngai Shing Development Limited

香港九龍長沙灣永康街52號地下

G/F., 52 Wing Hong St.,

Cheung Sha Wan, Kln., Hong Kong.

Tel: (852) 2741 9981, 2742 0078

E-MAIL: info@ngaishing.com

Fax: (852) 2785 3149

Http://www.ngaishing.com