

NS-3701

全蒸汽熨斗 (手按式)

Steam Heated Iron (Press Handle Type)




- 最適用針織、合成纖維的整燙
- 底板與蒸汽室一體結構，升溫迅速
- 采用蒸汽循環加熱方式，實現在低溫下熨燙操作
- 手按式高性能蒸汽閥，輕鬆、靈活控制蒸汽發生

選購件：

C28-010-03-1 熨斗鞋 (讓您遠離布料因對溫度敏感而產生鏡面現象的煩惱)

C18-S-02-2E 疏水閥



- Best for ironing knitted and synthetic fiber
- Iron sole and steam chamber are as a whole, temperature rising quickly
- Apply steam circulation heating mode, it could be operated in low temperature
- Swing handle type steam valve for adjusting steam volume flexibly

Options:

C28-010-03-1 Special designed Teflon shoe (Its thermal insulation helps you get rid of the annoyance caused by heat sensitive fabric)

C18-S-02-2E Steam trap




1. 採用蒸汽循環加熱方式，實現低溫熨燙都不會漏水
2. 蒸汽室連底板採用不銹鋼製造
3. 蒸汽孔位多，可噴蒸汽量大，最適於熨燙較厚面料衣物



1. Apply steam circulation heating mode, there is no water leakage even when ironing in lower temperature
2. Steam chamber with sole is made of stainless steel
3. Many steam holes could spray large amounts of steam, which is best for ironing thick fabric

熨斗尺寸簡圖 Iron Dimensions Diagram (mm)

選購件 Options



C18-S-02-2E
疏水閥(1/4")
Steam Trap(1/4")

C28-010-03-1
熨鬥鞋
Teflon Shoe

C31-CES-10-33M
吊熨鬥彈簧
Iron Hanging Spring

跟機件 Delivered



C33-00082
燙鬥墊
iron pad

C17-RP-004-1M
3米原子喉連接頭×2條
3m Teflon hose with
fitting × 2 pcs

APT15-00068
布套
Cloth Sleeve

易損件 Wearings



C33-3702-8
蒸汽開關
Steam Valve

C33-3702-5
排水閥
Water Outlet Valve

C33-3700-3
熨鬥手柄
Iron Handle

型號 Model	蒸汽壓力(kgf/cm ²) Steam Pressure	蒸汽開關 Steam Valve	耗蒸汽量(kg/h) Steam Consumption	最高設計溫度(°C) Max. Designed Temp.	淨重(kg) Net Weight	熨鬥底尺寸(mm) Sole Size
NS-3701	3~5	手按式 Press handle type	5	135	1.5	203x140



藝誠(余氏)發展有限公司
Ngai Shing Development Limited

香港九龍長沙灣永康街52號地下
G/F., 52 Wing Hong St.,
Cheung Sha Wan, Kln., Hong Kong.

Tel: (852) 2741 9981, 2742 0078 E-MAIL: info@ngaishing.com
Fax: (852) 2785 3149 Http://www.ngaishing.com