

NS-47U 氣動釘鈕機—連十字定位燈及安全罩 Pneumatic Snap Fixing Machine with Light Marker & Safety Guard




珍珠鈕 Pearl Button



工字扣 Jeans Button



五爪鈕 Five claw button



檯面板 Table top



在工作中，安全環下移到位后沖頭才能開始釘鈕動作；若中途有任何障礙物碰到安全環，安全裝置都會阻止沖頭下移，提高操作安全

During working, the punching head could start punching only when the safety ring reaches a fixed position, if any object touches it, it will act and prevent the punching head from moving down, in this way the operation safety is ensured

- 適用於沖壓衣物上或真皮、塑膠布料上的鐵鈕、膠鈕、珍珠鈕、工字扣等鈕扣
- 採用氣動加壓，加壓壓力可調，沖力強中帶柔，沖壓效果佳
- 沖壓到尾時能停在可調校的指定時間後回位，使鈕扣更堅固沖合
- 十字鐳射定位燈，定位準確，操作簡便
- 安全防護裝置帶有導軌設計，操作安全

選購件：各種鈕模、檯面板(O-G-03-1)

- For punching iron button, plastic button, pearl button and jeans button on garment, genuine leather, plastic fabric, etc.
- Adopt air cylinder to drive and punching pressure is adjustable. Regardless of strong power, it retains a touch of tenderness while pressing the buttons, thereby to achieve superb effect
- Before return, the punching head can dwell for a short time(adjustable) at stroke end to ensure robust quality of the button pieces' joint
- Cross laser marker for accurate positioning and easy operation
- Ensured operational safety by the protective guard with guide rail

Options: Various button moulds, Table top (O-G-03-1)

型號 Model	電源 Power Supply	總功率(kW) Total Power	壓縮空氣壓力(kgf/cm ²) Compressed Air Pressure	耗壓縮空氣量 (L/min) Compressed Air Consumption	最大沖程(mm) Max. Stroke	最大壓力(kgf/cm ²) Max. Pressure	淨重(kg) Net Weight	機身尺寸 (mm) Machine Size
NS-47U	1PH/220V/50Hz	0.1	5	30	50	390	62	620x410x1320



藝誠(余氏)發展有限公司
Ngai Shing Development Limited

香港九龍長沙灣永康街52號地下

G/F., 52 Wing Hong St.,

Cheung Sha Wan, Kln., Hong Kong.

Tel: (852)2741 9981, 2742 0078

E-MAIL: info@ngaishing.com

Fax: (852)2785 3149

Http://www.ngaishing.com