


Wassar 30S / 50S / 50H / 80S / 160S

自動洗衣脫水機

Automatic Washing Extractor



Wassar 30S

- 適用於襯衫、針織等衣物洗滌
- 前置式結構，水比小，配合變頻調速，滿足多種洗滌要求，降低洗衣成本
- 採用PLC可編程控制器控制及人性化操作界面觸摸顯示屏操作，可記憶多種洗衣程式及多個步驟
- 採用蒸汽直接加熱，即時/到溫計時選擇
- 本機標配一套電控氣動入水系統
- 配有手動加藥系統
- 採用懸浮式避振裝置，有效降低機器運轉時產生的振動
- 具有自動脫水功能，極大地節省人力並顯著地提高生產效率

選購件：

VaporTec 10 / 20 / 100

- Suitable for shirt, knitwear, etc. washing
- Front loading design, low liquor ratio, and inverter speed control; it can satisfy various wash requirements at low operating cost
- Adopt PLC and user friendly touch screen for operation; can store a variety of programs with several steps
- Direct steam heating, immediate/up-to temperature timing modes available for selection
- With one set of electric controlled pneumatic water feeding system
- With manual chemical feeding system
- Adopts suspension type vibration absorbing device for less vibration during machine running
- With automatic extracting function, saving labor and high efficiency

Option:

VaporTec 10 / 20 / 100

型號 Model	容積(m ³) Volume	電源 Power Supply	馬達(kW) Motor	內膽尺寸(mm) Inner Drum Size	外膽尺寸(mm) Outer Drum Size	洗水轉速 (RPM) Washing Speed	脫水轉速 (RPM) Extracting Speed	機身尺寸(mm) Machine Size
Wassar 30S	0.3	3PH/380V/50Hz	3	Ø900x496x2	Ø973x640x2	20~36	600	1600x1500x2000
Wassar 50S	0.5		3	Ø1080x625x2	Ø1200x735x2	25~40	600	1620x1700x2050*
Wassar 50H	0.5		3	Ø1080x625x2	Ø1200x735x2	25~40	1000	1620x1700x2050*
Wassar 80S	0.8		7.5	Ø1200x750x3	Ø1280x910x3	20~35	500	2000x2110x2150*
Wassar 160S	1.6		15	Ø1470x905x3	Ø1540x1125x3	20~35	400	1980x2350x2110*



藝誠(余氏)發展有限公司
Ngai Shing Development Limited

香港九龍長沙灣永康街52號地下

G/F., 52 Wing Hong St.,

Cheung Sha Wan, Kln., Hong Kong.

Tel : (852)2741 9981, 2742 0078

Fax: (852)2785 3149

E-MAIL: info@ngaishing.com

Http://www.ngaishing.com