

Actmix®Pb₃O₄-80GE Pre-dispersed rubber vulcanizing activator

FUNCTION	vulcanizing activator	
DESCRIPTION OF PRODUCTS	Compositon	80% Red lead oxide, 20% Rubber carrier, Dispersant
	Appearance	Orange Granules
	Density (20 °C)	About 3.2g/cm ³
	Security character	Please refer to related SDS
APPLICATION DATA		
PROPERTIES	Pb ₃ O ₄ -80GE is a vulcanizing activator for CR IIR CSM rubber, can have the effect of X-ray absorption in rubber. It commonly used as acid compound activator, it greatly promotes the swelling of rubber vulcanization in water. It can also be used as an activator for vulcanization of butyl rubber and quinone two oxime.	
DOSAGE	5-20phr	
APPLICATION	Waterproof rubber, butyl and chloroprene rubber vulcanizing activator.	
PACKAGING	Net weight 25kg/PE bags lined carton; Net weight 1000 kg/pallet.	
STORAGE	Stored in a dry and cool place. Shelf-life: 2 year in its original packaging	
DISPOSITION	Chemical additives in the rubber processing work area suggest convulsions exhaust, further disposal data refer to Actmix®Pb ₃ O ₄ -80GE safety data sheets.	

G: granule, P: plate, E: EPDM binder, N: NBR binder, S: SBR binder, A: ACM binder, EO: ECO binder.

The information contained in this leaflet is based on tests carried out by our laboratories and data selected from references. Therefore it is not valid legally and does not signify any guarantee to customers of successful applications of the product according to their own formulas. However, our company will offer professional services in technology at utmost to facilitate customers to achieve expected purpose of product applications.